



YEAR 2004
CORE STATION 5022
ROAD NETWORK MAJOR
ROAD TYPE URBAN TRUNK ROAD

LINK TATE'S CAIRN TUNNEL (from TOLL PLAZA to SOUTH PORTAL)



1. TRAFFIC FLOW VARIATION AND GROWTH



2. TRAFFIC CHARACTERISTICS (BY DIRECTION)

Parameter	All - Day	Mon. - Fri.	Sat.	Sun.
SOUTH BOUND				
A.A.D.T.	29380	30350	32250	23950
R 12 / 24 - %	74.9	76.2	74	67.7
R 16 / 24 - %	90.1	90.5	89.4	88.3
AM Peak Hour	0800-0900	0800-0900	0800-0900	0900-1000
One-way flow at AM peak hour	2740	3090	2970	1190
T - % (AM)	-	14.5	-	-
PM Peak Hour	1800-1900	1800-1900	1800-1900	1800-1900
One-way flow at PM peak hour	2100	2150	2220	1900
T - % (PM)	-	11.4	-	-
Prop.of commercial vehicles - 16 hr.	-	15.1	-	-
NORTH BOUND				
A.A.D.T.	31230	32300	34730	24840
R 12 / 24 - %	66	66.5	66.7	61.5
R 16 / 24 - %	87.8	88.3	86.3	86.8
AM Peak Hour	0800-0900	0800-0900	0900-1000	0900-1000
One-way flow at AM peak hour	1990	2310	1750	980
T - % (AM)	-	13.2	-	-
PM Peak Hour	1800-1900	1800-1900	1800-1900	1700-1800
One-way flow at PM peak hour	2520	2780	2440	1540
T - % (PM)	-	11.4	-	-
Prop.of commercial vehicles - 16 hr.	-	14.6	-	-

3. OTHER INFORMATION AND COMMENT

4. Vehicle classification and occupancy - Monday to Friday

Time		Class of vehicle									
		Motor	Private	Taxi	Private	PLB	Goods veh.		Non	Fr. Bus	
		Cycle	Car		LB		Light	M & H	Fr. Bus	SD	DD
0700-0800	Pro	4.9	55.2	8.9	0.2	0.0	12.5	6.3	4.6	0.0	7.3
	Ocp	1.1	1.7	2.1	12.5	0.0	1.9	1.2	28.4	0.0	68.7
0800-0900 Peak hour	Pro	4.1	59.4	8.0	0.4	0.1	14.0	4.0	3.9	0.0	6.1
	Ocp	1.2	1.4	1.9	2.0	1.0	1.6	1.3	34.5	0.0	75.9
0900-1000	Pro	2.6	53.2	10.8	0.6	0.0	17.8	7.7	1.4	0.0	5.9
	Ocp	1.1	1.3	1.7	2.4	0.0	1.8	1.4	22.3	0.0	41.0
1000-1100	Pro	2.4	49.7	9.3	0.6	0.0	22.0	7.9	1.8	0.0	6.3
	Ocp	1.1	1.4	1.9	1.2	0.0	1.7	1.5	12.4	0.0	35.0
1100-1200	Pro	1.8	49.1	7.7	0.4	0.0	22.8	11.5	0.9	0.0	5.7
	Ocp	1.1	1.3	2.0	1.7	0.0	1.6	1.5	12.8	0.0	28.8
1200-1300	Pro	2.3	54.1	7.2	0.1	0.0	18.5	10.7	0.4	0.0	6.6
	Ocp	1.1	1.4	1.9	1.0	0.0	1.6	1.3	12.0	0.0	25.5
1300-1400	Pro	1.4	43.0	7.0	0.8	0.0	26.7	13.4	1.2	0.0	6.5
	Ocp	1.0	1.5	1.9	1.6	0.0	1.7	1.5	22.0	0.0	30.4
1400-1500	Pro	2.0	48.0	5.9	0.8	0.0	26.1	10.4	1.0	0.0	5.7
	Ocp	1.1	1.4	2.0	2.8	0.0	1.6	1.4	18.4	0.0	28.4
1500-1600	Pro	1.5	48.6	9.5	0.7	0.0	23.1	9.9	0.7	0.0	6.0
	Ocp	1.1	1.4	1.7	2.4	0.0	1.6	1.4	30.2	0.0	28.0
1600-1700	Pro	3.2	47.8	10.8	1.0	0.0	22.1	6.4	1.9	0.0	6.8
	Ocp	1.0	1.6	1.4	3.9	0.0	1.6	1.5	18.9	0.0	34.3
1700-1800	Pro	3.4	56.0	7.7	0.2	0.0	18.3	5.7	1.4	0.0	7.2
	Ocp	1.1	1.5	1.7	3.0	0.0	1.7	1.4	15.8	0.0	42.3
1800-1900	Pro	2.8	66.1	7.3	0.7	0.0	11.7	2.9	2.1	0.0	6.3
	Ocp	1.1	1.5	2.0	5.0	0.0	1.6	1.4	32.6	0.0	65.0
1900-2000	Pro	1.7	70.6	7.5	0.5	0.0	8.1	2.9	2.2	0.0	6.5
	Ocp	1.1	1.4	2.0	1.8	0.0	1.5	1.4	17.4	0.0	64.1
2000-2100	Pro	2.8	70.2	8.7	0.8	0.0	7.5	2.2	0.8	0.0	7.1
	Ocp	1.2	1.5	2.1	2.8	0.0	1.6	1.2	10.8	0.0	49.8
2100-2200	Pro	4.2	64.3	11.6	0.0	0.0	7.1	3.5	0.8	0.0	8.5
	Ocp	1.1	1.5	2.0	0.0	0.0	1.5	1.5	25.8	0.0	45.1
2200-2300	Pro	4.4	67.9	13.8	0.2	0.0	3.4	0.7	1.6	0.0	8.0
	Ocp	1.3	1.4	2.2	1.0	0.0	1.6	1.3	16.7	0.0	41.5
16 hours	Pro	2.9	56.7	8.7	0.5	0.1	16.3	6.4	1.9	0.0	6.6
	Ocp	1.1	1.4	1.9	3.0	1.0	1.6	1.4	24.8	0.0	47.1

Legend

- Pro.** Proportion of vehicles in % (Sum may not add up to 100% due to figure rounding)
- Ocp.** Average occupancy of vehicles
- M&H** Medium and Heavy