

YEAR

2004

LINK

SHANGHAI ST (from DUNDAS ST to ARGYLE ST)

COVERAGE (B) STATION


4209

ROAD NETWORK






MAJOR

ROAD TYPE

DISTRICT DISTRIBUTOR



1. TRAFFIC FLOW VARIATION AND GROWTH



2. TRAFFIC CHARACTERISTICS (BY DIRECTION)

Parameter	All - Day	Mon. - Fri.	Sat.	Sun.
SOUTH BOUND				
A.A.D.T.	18100	18620	19150	15530
R 12 / 24 - %	55.3	56.2	55.5	50
R 16 / 24 - %	73.2	74.1	73.1	67.6
AM Peak Hour	0900-1000	0900-1000	0900-1000	0800-0900
One-way flow at AM peak hour	690	740	720	510
T - % (AM)	-	8.5	-	-
PM Peak Hour	1800-1900	1800-1900	1800-1900	1800-1900
One-way flow at PM peak hour	1010	1060	1020	800
T - % (PM)	-	3.9	-	-
Prop.of commercial vehicles - 16 hr.	-	6.1	-	-
 A.A.D.T.	-	-	-	-
R 12 / 24 - %	-	-	-	-
R 16 / 24 - %	-	-	-	-
AM Peak Hour	-	-	-	-
One-way flow at AM peak hour	-	-	-	-
T - % (AM)	-	-	-	-
PM Peak Hour	-	-	-	-
One-way flow at PM peak hour	-	-	-	-
T - % (PM)	-	-	-	-
Prop.of commercial vehicles - 16 hr.	-	-	-	-

3. OTHER INFORMATION AND COMMENT

Coverage (B) Station 4209
Year 2004

4. Vehicle classification and occupancy - Monday to Friday

Time		Class of vehicle									
		Motor	Private	Taxi	Private	PLB	Goods veh.		Non	Fr. Bus	
		Cycle	Car		LB		Light	M & H	Fr. Bus	SD	DD
0700-0800	Pro	0.0	3.2	39.3	2.1	19.1	19.1	1.1	11.7	1.1	3.4
	Ocp	0.0	2.7	1.4	8.5	7.4	1.4	1.0	19.4	19.0	16.6
0800-0900	Pro	2.3	14.8	16.5	1.1	19.9	21.7	4.6	16.5	0.4	2.1
	Ocp	1.0	1.3	1.9	2.0	9.2	1.6	1.5	37.2	19.3	19.9
0900-1000	Pro	2.7	14.0	21.0	0.5	14.5	38.8	3.2	2.7	0.4	2.2
	Ocp	1.0	1.3	1.5	10.0	7.8	1.8	2.0	34.8	8.7	15.6
1000-1100	Pro	1.7	18.9	30.3	1.7	11.8	28.2	5.0	0.8	0.3	1.4
	Ocp	1.0	1.4	1.4	2.8	5.9	1.7	2.3	1.0	4.0	14.8
1100-1200	Pro	0.5	14.2	31.5	1.4	14.2	32.5	4.1	0.0	0.3	1.4
	Ocp	1.0	1.4	1.4	3.3	5.5	1.7	1.8	0.0	5.0	13.1
1200-1300	Pro	2.3	18.2	28.3	0.8	11.3	31.8	3.9	1.9	0.3	1.2
	Ocp	1.0	1.3	1.3	5.0	6.7	1.8	1.8	7.8	4.3	13.8
1300-1400	Pro	3.1	15.2	26.8	1.8	13.4	32.7	4.5	0.9	0.3	1.2
	Ocp	1.1	1.3	1.4	2.8	6.2	1.6	1.8	20.5	3.7	14.9
1400-1500	Pro	2.7	17.5	32.6	0.8	10.5	32.6	1.9	0.0	0.3	1.2
	Ocp	1.1	1.4	1.3	4.0	8.3	1.7	1.6	0.0	5.0	13.0
1500-1600 Peak hour	Pro	2.0	19.0	30.0	2.0	13.3	30.0	1.7	0.7	0.3	1.0
	Ocp	1.2	1.5	1.4	2.8	7.0	1.6	1.8	1.0	5.0	13.2
1600-1700	Pro	2.6	21.7	24.7	0.0	17.9	28.1	2.6	1.3	0.2	1.2
	Ocp	1.0	1.6	1.4	0.0	5.9	1.5	1.7	2.3	4.0	8.5
1700-1800	Pro	5.0	23.4	31.1	1.2	13.1	22.3	1.2	1.2	0.5	1.2
	Ocp	1.1	1.7	1.5	2.7	7.0	1.8	1.3	20.3	3.4	10.5
1800-1900	Pro	1.4	28.6	32.1	0.7	17.5	15.7	1.0	1.7	0.3	0.9
	Ocp	1.3	1.5	1.4	8.5	8.9	1.6	1.7	16.0	9.0	17.4
1900-2000	Pro	2.3	30.4	37.6	0.8	20.5	5.3	1.1	0.8	0.3	1.0
	Ocp	1.0	1.6	1.7	15.5	5.4	1.3	1.0	1.5	9.0	12.5
2000-2100	Pro	1.4	27.4	36.6	1.4	20.6	10.1	0.5	0.9	0.3	0.9
	Ocp	1.0	1.5	1.3	1.7	4.6	1.5	2.0	1.0	5.7	11.4
2100-2200	Pro	1.9	25.7	48.5	0.0	13.3	7.1	1.0	1.0	0.2	1.4
	Ocp	1.0	1.5	1.5	0.0	4.9	1.5	2.0	1.0	3.5	5.1
2200-2300	Pro	2.4	28.7	31.7	0.6	23.4	9.6	1.2	0.6	0.2	1.6
	Ocp	1.5	1.8	1.5	5.0	4.0	2.2	1.0	1.0	4.0	6.0
16 hours	Pro	2.2	20.9	31.1	1.0	15.5	23.1	2.4	2.1	0.3	1.3
	Ocp	1.1	1.5	1.4	4.4	6.5	1.7	1.8	23.0	7.4	13.1

Legend

- Pro.** Proportion of vehicles in % (Sum may not add up to 100% due to figure rounding)
- Ocp.** Average occupancy of vehicles
- M&H** Medium and Heavy