







YEAR 2004  
CORE STATION 5017  
ROAD NETWORK MAJOR  
ROAD TYPE RURAL ROAD

LINK CLEAR WATER BAY RD (from ANDERSON RD to  
HIRAM'S HIGHWAY)



## 1. TRAFFIC FLOW VARIATION AND GROWTH



## 2. TRAFFIC CHARACTERISTICS (BY DIRECTION)

Parameter	All - Day	Mon. - Fri.	Sat.	Sun.
<b>EAST BOUND</b>				
A.A.D.T.	15070	14680	16800	15330
R 12 / 24 - %	62.6	62.4	63.3	62.8
R 16 / 24 - %	85.7	86.5	84.6	83.6
AM Peak Hour	0800-0900	0800-0900	0900-1000	0900-1000
One-way flow at AM peak hour	830	880	810	740
T - % (AM)	-	8.9	-	-
PM Peak Hour	1800-1900	1800-1900	1800-1900	1600-1700
One-way flow at PM peak hour	1110	1140	1140	940
T - % (PM)	-	5	-	-
Prop.of commercial vehicles - 16 hr.	-	7.4	-	-
<b>WEST BOUND</b>				
A.A.D.T.	15790	15510	17350	15670
R 12 / 24 - %	72.5	74.6	69	66.1
R 16 / 24 - %	87.9	88.7	86.5	85.6
AM Peak Hour	0800-0900	0800-0900	0800-0900	0900-1000
One-way flow at AM peak hour	1460	1660	1340	760
T - % (AM)	-	6.8	-	-
PM Peak Hour	1700-1800	1700-1800	1800-1900	1800-1900
One-way flow at PM peak hour	1020	990	1140	1200
T - % (PM)	-	7.1	-	-
Prop.of commercial vehicles - 16 hr.	-	7.1	-	-

## 3. OTHER INFORMATION AND COMMENT

**4. Vehicle classification and occupancy - Monday to Friday**

Time		Class of vehicle									
		Motor	Private	Taxi	Private	PLB	Goods veh.		Non	Fr. Bus	
		Cycle	Car		LB		Light	M & H	Fr. Bus	SD	DD
0700-0800	Pro	5.7	43.3	10.6	4.4	16.3	10.9	2.2	4.4	0.1	2.2
	Ocp	1.0	1.6	1.9	7.4	14.6	1.6	1.0	9.3	1.0	46.7
0800-0900 Peak hour	Pro	4.5	58.5	8.4	2.1	9.1	9.9	3.3	3.1	0.0	1.2
	Ocp	1.2	1.5	1.8	7.3	14.2	1.7	1.3	17.9	0.0	53.5
0900-1000	Pro	2.7	56.3	7.2	1.0	9.9	14.8	2.3	4.1	0.0	1.7
	Ocp	1.2	1.5	1.7	5.0	12.7	1.6	1.0	28.7	0.0	33.6
1000-1100	Pro	3.9	50.1	6.2	1.1	12.1	18.6	5.1	1.1	0.0	1.8
	Ocp	1.0	1.4	1.5	2.8	11.0	1.6	1.2	5.3	0.0	27.6
1100-1200	Pro	3.1	50.6	7.7	3.4	10.8	17.9	2.8	2.2	0.0	1.6
	Ocp	1.0	1.5	2.0	2.3	9.4	1.6	1.3	9.6	0.0	26.2
1200-1300	Pro	4.3	47.5	6.1	5.8	13.4	14.3	4.3	2.7	0.0	1.8
	Ocp	1.0	1.4	2.0	8.8	7.5	1.7	1.3	14.2	0.0	29.6
1300-1400	Pro	3.7	46.1	7.2	5.3	9.0	18.1	3.1	5.6	0.0	1.9
	Ocp	1.0	1.5	2.0	6.4	12.4	1.6	1.3	12.9	0.0	28.0
1400-1500	Pro	3.7	42.1	6.4	4.7	10.4	22.7	5.7	2.3	0.0	2.1
	Ocp	1.2	1.4	1.5	1.8	7.6	1.5	1.4	11.1	0.0	29.0
1500-1600	Pro	3.8	45.4	8.6	3.2	10.2	17.3	6.4	3.2	0.0	1.9
	Ocp	1.1	1.6	1.7	2.3	9.8	1.8	1.2	4.9	0.0	31.8
1600-1700	Pro	3.5	50.1	7.1	2.7	8.2	18.3	4.6	3.5	0.0	1.9
	Ocp	1.2	1.6	1.3	2.7	13.6	1.5	1.2	12.5	0.0	48.0
1700-1800	Pro	6.0	48.1	7.6	3.3	12.8	14.1	2.8	3.5	0.0	1.8
	Ocp	1.0	1.5	1.9	3.5	14.0	1.7	1.1	10.1	0.0	49.3
1800-1900	Pro	4.1	63.1	8.5	1.6	11.0	6.9	1.2	2.0	0.1	1.6
	Ocp	1.2	1.6	1.7	4.6	15.1	1.6	1.0	6.4	1.0	45.4
1900-2000	Pro	2.9	65.9	8.8	0.5	12.5	6.9	0.5	0.7	0.0	1.2
	Ocp	1.0	1.6	1.7	2.0	10.3	1.4	1.0	5.7	0.0	24.2
2000-2100	Pro	1.7	62.0	11.8	0.3	14.2	6.2	0.0	1.7	0.0	1.9
	Ocp	1.2	1.3	1.5	1.0	9.9	1.4	0.0	2.4	0.0	18.3
2100-2200	Pro	4.1	60.5	13.3	0.7	12.7	4.1	0.3	2.1	0.0	2.2
	Ocp	1.0	1.4	1.8	3.5	10.2	1.3	1.0	5.0	0.0	16.8
2200-2300	Pro	4.5	60.6	12.4	2.1	11.8	6.1	0.6	0.0	0.0	1.9
	Ocp	1.1	1.5	1.6	2.4	10.2	1.4	1.0	0.0	0.0	21.6
16 hours	Pro	3.9	53.7	8.5	2.5	11.4	12.7	2.8	2.7	0.1	1.8
	Ocp	1.1	1.5	1.7	4.8	11.7	1.6	1.2	12.8	1.0	34.2

**Legend**

- Pro.** Proportion of vehicles in % (Sum may not add up to 100% due to figure rounding)
- Ocp.** Average occupancy of vehicles
- M&H** Medium and Heavy