


YEAR






2004

LINK

TAI PO RD (from NAM CHEONG ST to KWEILIN ST)

CORE STATION  
ROAD NETWORK  
ROAD TYPE3009  
MAJOR  
PRIMARY DISTRIBUTOR

## 1. TRAFFIC FLOW VARIATION AND GROWTH



## 2. TRAFFIC CHARACTERISTICS (BY DIRECTION)

Parameter	All - Day	Mon. - Fri.	Sat.	Sun.
<b>SOUTH BOUND</b>				
A.A.D.T.	10640	10880	11280	9530
R 12 / 24 - %	60.4	61.7	58.8	54.4
R 16 / 24 - %	76.3	77.7	74.3	71
AM Peak Hour	0800-0900	0800-0900	0900-1000	0900-1000
One-way flow at AM peak hour	580	650	610	380
T - % (AM)	-	-	-	-
PM Peak Hour	1800-1900	1800-1900	1800-1900	1700-1800
One-way flow at PM peak hour	580	610	570	500
T - % (PM)	-	-	-	-
Prop.of commercial vehicles - 16 hr.	-	-	-	-
<b>NORTH BOUND</b>				
A.A.D.T.	6280	6590	6700	4680
R 12 / 24 - %	62.5	64	62.9	51.1
R 16 / 24 - %	80.7	81.9	80.5	72.9
AM Peak Hour	0900-1000	0900-1000	0900-1000	0900-1000
One-way flow at AM peak hour	270	300	280	150
T - % (AM)	-	-	-	-
PM Peak Hour	1800-1900	1800-1900	1700-1800	1600-1700
One-way flow at PM peak hour	430	470	430	270
T - % (PM)	-	-	-	-
Prop.of commercial vehicles - 16 hr.	-	-	-	-

## 3. OTHER INFORMATION AND COMMENT