

YEAR 2005

COVERAGE (B) STATION 2201






ROAD NETWORK MAJOR

ROAD TYPE PRIMARY DISTRIBUTOR

LINK POK FU LAM RD (from POKFIELD RD to MOUNT DAVIS RD)



1. TRAFFIC FLOW VARIATION AND GROWTH



2. TRAFFIC CHARACTERISTICS (BY DIRECTION)

Parameter	All - Day	Mon. - Fri.	Sat.	Sun.
SOUTH BOUND				
A.A.D.T.	11890	12380	12260	9800
R 12 / 24 - %	67.7	68.6	67.9	62.2
R 16 / 24 - %	88.2	89.4	86.1	83.8
AM Peak Hour	0900-1000	0900-1000	0900-1000	0900-1000
One-way flow at AM peak hour	750	820	750	440
T - % (AM)	-	11.1	-	-
PM Peak Hour	1800-1900	1800-1900	1600-1700	1600-1700
One-way flow at PM peak hour	770	830	760	570
T - % (PM)	-	13	-	-
Prop.of commercial vehicles - 16 hr.	-	11.6	-	-
NORTH BOUND				
A.A.D.T.	16270	16950	16870	13300
R 12 / 24 - %	71.1	72.2	70.2	65.1
R 16 / 24 - %	88.5	89.5	86.6	84.6
AM Peak Hour	0800-0900	0800-0900	0900-1000	0900-1000
One-way flow at AM peak hour	1300	1510	1140	680
T - % (AM)	-	9.2	-	-
PM Peak Hour	1800-1900	1800-1900	1800-1900	1800-1900
One-way flow at PM peak hour	1030	1090	990	840
T - % (PM)	-	7.5	-	-
Prop.of commercial vehicles - 16 hr.	-	9.3	-	-

3. OTHER INFORMATION AND COMMENT

Coverage (B) Station 2201
Year 2005

4. Vehicle classification and occupancy - Monday to Friday

Time		Class of vehicle									
		Motor	Private	Taxi	Private	PLB	Goods veh.		Non	Fr. Bus	
		Cycle	Car		LB		Light	M & H	Fr. Bus	SD	DD
0700-0800	Pro	2.0	23.1	31.4	2.2	16.4	8.2	0.5	8.7	0.3	7.1
	Ocp	1.3	1.8	2.1	5.0	12.1	1.5	1.0	17.7	25.6	58.2
0800-0900 Peak hour	Pro	1.6	38.2	28.7	1.9	14.6	4.7	0.7	4.1	0.3	5.2
	Ocp	1.2	1.5	2.1	5.7	13.2	1.6	1.5	11.1	22.3	56.8
0900-1000	Pro	1.6	37.6	29.9	2.2	12.7	8.7	1.0	0.2	0.4	5.8
	Ocp	1.0	1.5	1.9	3.3	11.7	1.5	1.4	1.0	11.1	33.1
1000-1100	Pro	1.9	26.0	34.6	1.9	10.7	17.2	0.6	1.0	0.3	5.9
	Ocp	1.1	1.5	1.9	2.8	9.9	1.7	2.3	1.4	14.8	19.0
1100-1200	Pro	3.4	27.1	27.4	4.2	13.7	12.4	0.5	3.4	0.3	7.6
	Ocp	1.0	1.6	2.0	2.3	9.1	1.8	2.5	4.5	5.8	17.2
1200-1300	Pro	1.1	29.3	26.0	2.7	13.7	15.9	0.3	3.3	0.5	7.2
	Ocp	1.0	1.8	2.1	3.6	10.5	1.7	2.0	8.3	7.6	20.1
1300-1400	Pro	3.0	23.2	32.1	1.4	13.8	15.2	1.1	1.9	0.4	7.8
	Ocp	1.1	1.5	2.0	5.8	12.2	1.8	2.0	2.9	12.5	17.9
1400-1500	Pro	2.4	32.0	28.8	2.9	12.8	12.3	0.3	1.1	0.5	7.1
	Ocp	1.0	1.6	2.0	3.3	11.3	1.9	2.0	25.0	9.6	25.1
1500-1600	Pro	2.0	23.4	29.6	4.1	13.4	18.0	0.7	2.3	0.3	6.2
	Ocp	1.1	1.7	2.1	2.1	9.1	1.9	2.3	16.4	13.0	24.2
1600-1700	Pro	3.9	22.7	28.6	3.9	13.5	14.9	1.1	3.9	0.3	7.1
	Ocp	1.1	1.7	1.8	3.9	11.8	1.7	1.8	6.2	13.0	35.2
1700-1800	Pro	2.5	34.2	24.2	0.9	14.8	11.2	0.9	3.1	0.4	7.8
	Ocp	1.2	1.5	1.8	4.5	11.5	2.1	1.5	6.4	19.9	38.0
1800-1900	Pro	3.5	36.1	28.3	1.1	14.7	6.7	0.2	2.2	0.3	7.0
	Ocp	1.0	1.5	1.7	1.8	13.5	1.8	1.0	16.7	15.8	49.1
1900-2000	Pro	1.4	31.4	39.3	0.5	14.3	3.8	0.0	1.4	0.4	7.4
	Ocp	1.2	1.6	1.8	2.0	12.9	1.4	0.0	4.7	10.7	33.6
2000-2100	Pro	1.3	29.9	42.2	0.5	16.9	1.6	0.3	0.3	0.3	6.8
	Ocp	1.0	1.5	1.9	2.0	7.9	1.3	1.0	3.0	11.0	25.3
2100-2200	Pro	2.6	24.5	48.7	0.3	14.7	1.0	0.0	0.0	0.5	7.7
	Ocp	1.0	1.5	1.6	4.0	8.3	2.0	0.0	0.0	9.2	18.3
2200-2300	Pro	1.2	24.7	43.3	0.8	17.8	2.0	0.0	0.0	0.4	9.8
	Ocp	1.0	1.5	1.7	2.5	7.8	2.2	0.0	0.0	6.5	15.1
16 hours	Pro	2.2	29.6	32.0	2.0	14.1	9.8	0.5	2.4	0.4	6.9
	Ocp	1.1	1.6	1.9	3.4	11.0	1.8	1.8	10.9	13.2	31.3

Legend

- Pro.** Proportion of vehicles in % (Sum may not add up to 100% due to figure rounding)
- Ocp.** Average occupancy of vehicles
- M&H** Medium and Heavy