

YEAR


2006

LINK






KO SHAN RD (from PAK KUNG ST to CHI KIANG ST)

CORE STATION  
ROAD NETWORK  
ROAD TYPE

3103  
MINOR  
LOCAL DISTRIBUTOR



### 1. TRAFFIC FLOW VARIATION AND GROWTH



### 2. TRAFFIC CHARACTERISTICS (BY DIRECTION)

Parameter	All - Day	Mon. - Fri.	Sat.	Sun.
<b>SOUTH BOUND</b>				
A.A.D.T.	3750	3780	3950	3490
R 12 / 24 - %	67.1	67.6	67.1	64.3
R 16 / 24 - %	86.3	86.8	86	83.8
AM Peak Hour	0800-0900	0800-0900	0900-1000	0900-1000
One-way flow at AM peak hour	210	220	200	180
T - % (AM)	-	1.7	-	-
PM Peak Hour	1800-1900	1800-1900	1700-1800	1800-1900
One-way flow at PM peak hour	230	230	240	210
T - % (PM)	-	2.1	-	-
Prop.of commercial vehicles - 16 hr.	-	5.1	-	-
<b>NORTH BOUND</b>				
A.A.D.T.	4320	4300	4570	4220
R 12 / 24 - %	69.1	69.6	69	66.4
R 16 / 24 - %	87.1	87.5	87.1	85
AM Peak Hour	0900-1000	0900-1000	0900-1000	0900-1000
One-way flow at AM peak hour	280	280	300	260
T - % (AM)	-	-	-	-
PM Peak Hour	1600-1700	1600-1700	1600-1700	1800-1900
One-way flow at PM peak hour	240	240	260	230
T - % (PM)	-	4.8	-	-
Prop.of commercial vehicles - 16 hr.	-	4	-	-

### 3. OTHER INFORMATION AND COMMENT

**4. Vehicle classification and occupancy - Monday to Friday**

Time		Class of vehicle									
		Motor	Private	Taxi	Private	PLB	Goods veh.		Non	Fr. Bus	
		Cycle	Car		LB		Light	M & H	Fr. Bus	SD	DD
0700-0800	Pro	0.0	11.0	47.9	8.2	15.1	2.7	4.1	11.0	0.0	0.0
	Ocp	0.0	2.1	1.9	7.0	8.7	1.5	1.7	10.6	0.0	0.0
0800-0900	Pro	0.8	28.6	46.8	6.4	6.4	6.4	0.8	4.0	0.0	0.0
	Ocp	1.0	1.6	1.6	5.5	8.3	1.4	1.0	16.6	0.0	0.0
0900-1000	Pro	2.1	21.0	53.1	2.8	6.3	12.6	0.7	1.4	0.0	0.0
	Ocp	1.0	1.3	1.5	3.3	8.2	1.7	1.0	11.0	0.0	0.0
1000-1100	Pro	2.5	16.6	60.1	2.5	5.5	6.7	0.6	5.5	0.0	0.0
	Ocp	1.0	1.2	1.2	1.5	4.8	1.9	2.0	12.3	0.0	0.0
1100-1200	Pro	2.5	14.4	57.6	1.7	11.0	10.2	0.0	2.5	0.0	0.0
	Ocp	1.0	1.6	1.2	2.0	4.3	1.6	0.0	15.0	0.0	0.0
1200-1300	Pro	0.7	16.2	47.9	4.9	4.9	16.2	0.0	9.2	0.0	0.0
	Ocp	1.0	1.3	1.4	4.9	5.0	1.7	0.0	10.3	0.0	0.0
1300-1400 Peak hour	Pro	0.7	13.3	57.0	2.2	8.1	12.6	3.0	3.0	0.0	0.0
	Ocp	1.0	1.3	1.3	2.0	5.6	1.5	1.5	1.8	0.0	0.0
1400-1500	Pro	1.7	14.5	55.6	5.1	6.0	14.5	0.0	2.6	0.0	0.0
	Ocp	1.5	1.5	1.3	1.7	7.1	1.7	0.0	5.7	0.0	0.0
1500-1600	Pro	0.0	24.8	44.2	1.8	7.1	15.9	1.8	4.4	0.0	0.0
	Ocp	0.0	1.4	1.4	4.5	6.0	1.5	2.0	18.4	0.0	0.0
1600-1700	Pro	3.5	27.8	40.0	0.9	9.6	14.8	0.9	2.6	0.0	0.0
	Ocp	1.0	1.2	1.4	4.0	7.4	1.4	2.0	6.3	0.0	0.0
1700-1800	Pro	5.6	22.4	38.3	1.9	7.5	15.9	0.9	7.5	0.0	0.0
	Ocp	1.0	1.5	1.4	3.0	9.1	1.4	2.0	10.9	0.0	0.0
1800-1900	Pro	5.6	27.4	41.9	0.8	9.7	12.9	0.8	0.8	0.0	0.0
	Ocp	1.1	1.2	1.6	2.0	15.3	1.6	1.0	2.0	0.0	0.0
1900-2000	Pro	6.4	30.0	47.3	0.9	10.0	5.5	0.0	0.0	0.0	0.0
	Ocp	1.0	1.6	1.3	1.0	11.5	1.5	0.0	0.0	0.0	0.0
2000-2100	Pro	5.5	27.5	47.7	0.0	12.8	6.4	0.0	0.0	0.0	0.0
	Ocp	1.0	1.8	1.3	0.0	7.7	1.6	0.0	0.0	0.0	0.0
2100-2200	Pro	1.0	31.3	54.2	1.0	8.3	3.1	0.0	1.0	0.0	0.0
	Ocp	1.0	2.0	1.6	3.0	7.0	1.3	0.0	1.0	0.0	0.0
2200-2300	Pro	0.0	37.0	46.6	1.4	11.0	0.0	2.7	1.4	0.0	0.0
	Ocp	0.0	1.6	1.4	3.0	5.3	0.0	1.5	1.0	0.0	0.0
16 hours	Pro	2.5	22.2	49.6	2.6	8.3	10.3	0.9	3.5	0.0	0.0
	Ocp	1.0	1.5	1.4	3.8	7.7	1.6	1.6	10.7	0.0	0.0

**Legend**

- Pro.** Proportion of vehicles in % (Sum may not add up to 100% due to figure rounding)
- Ocp.** Average occupancy of vehicles
- M&H** Medium and Heavy