

YEAR

2006

LINK D'AGUILAR ST (from QUEEN'S RD C to WYNDHAM ST)

COVERAGE (B) STATION


2404

ROAD NETWORK






MINOR

ROAD TYPE

LOCAL DISTRIBUTOR



## 1. TRAFFIC FLOW VARIATION AND GROWTH



## 2. TRAFFIC CHARACTERISTICS (BY DIRECTION)

Parameter	All - Day	Mon. - Fri.	Sat.	Sun.
<b>SOUTH BOUND</b>				
A.A.D.T.	6830	6400	8490	7210
R 12 / 24 - %	51	54	44.5	44.7
R 16 / 24 - %	75.3	79.4	69.7	63.4
AM Peak Hour	0900-1000	0800-0900	0900-1000	0900-1000
One-way flow at AM peak hour	280	290	340	220
T - % (AM)	-	8.1	-	-
PM Peak Hour	1600-1700	1600-1700	1600-1700	1800-1900
One-way flow at PM peak hour	310	300	380	350
T - % (PM)	-	8.9	-	-
Prop.of commercial vehicles - 16 hr.	-	8.7	-	-

A.A.D.T.	-	-	-	-
R 12 / 24 - %	-	-	-	-
R 16 / 24 - %	-	-	-	-
AM Peak Hour	-	-	-	-
One-way flow at AM peak hour	-	-	-	-
T - % (AM)	-	-	-	-
PM Peak Hour	-	-	-	-
One-way flow at PM peak hour	-	-	-	-
T - % (PM)	-	-	-	-
Prop.of commercial vehicles - 16 hr.	-	-	-	-

## 3. OTHER INFORMATION AND COMMENT

**Coverage (B) Station 2404**  
**Year 2006**

**4. Vehicle classification and occupancy - Monday to Friday**

Time		Class of vehicle									
		Motor	Private	Taxi	Private	PLB	Goods veh.		Non	Fr. Bus	
		Cycle	Car		LB		Light	M & H	Fr. Bus	SD	DD
0700-0800	Pro	1.3	6.7	70.7	1.3	0.0	9.3	4.0	0.0	2.7	4.0
	Ocp	1.0	1.6	2.9	4.0	0.0	1.9	2.3	0.0	26.9	23.2
0800-0900	Pro	1.3	19.4	66.0	0.0	0.0	5.2	1.3	1.3	1.9	3.6
	Ocp	1.0	1.7	1.3	0.0	0.0	1.8	2.0	5.0	23.0	18.9
0900-1000	Pro	3.7	13.5	50.2	0.0	0.0	19.6	4.9	2.4	1.8	4.0
	Ocp	1.0	1.3	1.4	0.0	0.0	1.6	2.0	6.5	15.5	17.3
1000-1100	Pro	3.5	8.9	40.7	1.8	1.8	26.5	7.1	1.8	2.7	5.3
	Ocp	1.0	1.4	2.0	4.0	2.0	2.0	2.3	2.0	13.3	12.8
1100-1200	Pro	5.4	28.8	36.0	0.0	0.0	19.8	1.8	0.0	1.8	6.3
	Ocp	1.3	1.6	2.2	0.0	0.0	1.9	2.0	0.0	10.0	10.3
1200-1300	Pro	6.3	28.5	45.9	1.6	0.0	11.1	0.0	0.0	2.0	4.7
	Ocp	1.3	1.6	2.4	4.0	0.0	1.6	0.0	0.0	13.0	17.3
1300-1400	Pro	7.0	19.4	42.3	0.0	0.0	19.4	0.0	3.5	2.6	5.7
	Ocp	1.3	1.5	2.2	0.0	0.0	1.9	0.0	8.5	15.5	16.4
1400-1500	Pro	1.8	29.0	30.8	0.0	0.0	27.2	3.6	0.0	2.3	5.4
	Ocp	1.0	1.8	1.9	0.0	0.0	1.7	2.0	0.0	14.2	19.8
1500-1600	Pro	4.8	17.6	38.4	1.6	0.0	28.8	1.6	0.0	2.4	4.8
	Ocp	1.0	1.5	1.8	3.0	0.0	1.8	1.0	0.0	19.5	19.0
1600-1700	Pro	0.0	30.4	41.1	0.0	0.0	19.6	0.0	0.0	2.7	6.3
	Ocp	0.0	1.3	2.5	0.0	0.0	1.9	0.0	0.0	20.0	18.1
1700-1800	Pro	1.6	28.3	36.2	3.2	0.0	17.3	6.3	0.0	2.8	4.3
	Ocp	1.0	1.6	1.7	4.0	0.0	1.8	1.5	0.0	25.1	31.1
1800-1900	Pro	0.0	44.4	37.0	0.0	0.0	4.9	0.0	2.5	4.3	6.8
	Ocp	0.0	1.7	2.2	0.0	0.0	2.0	0.0	12.0	27.3	51.6
1900-2000	Pro	2.0	18.8	70.3	1.0	0.0	3.0	0.0	0.0	2.0	3.0
	Ocp	1.5	1.6	2.3	2.0	0.0	1.0	0.0	0.0	26.9	43.7
2000-2100 Peak hour	Pro	4.9	14.7	76.3	0.0	0.0	1.0	0.0	0.0	1.2	2.0
	Ocp	1.0	1.7	2.3	0.0	0.0	1.0	0.0	0.0	21.0	30.8
2100-2200	Pro	5.2	15.5	73.8	0.0	0.0	1.3	0.0	0.0	1.6	2.6
	Ocp	1.0	1.7	2.2	0.0	0.0	2.0	0.0	0.0	18.4	30.6
2200-2300	Pro	3.1	19.7	70.7	1.0	0.0	1.0	1.0	0.0	1.3	2.1
	Ocp	1.0	1.6	1.9	1.0	0.0	3.0	3.0	0.0	21.0	22.0
16 hours	Pro	3.3	20.2	55.1	0.7	0.1	12.0	1.9	0.6	2.1	4.1
	Ocp	1.1	1.6	2.1	3.3	2.0	1.8	2.0	7.0	20.2	23.2

**Legend**

- Pro.** Proportion of vehicles in % (Sum may not add up to 100% due to figure rounding)
- Ocp.** Average occupancy of vehicles
- M&H** Medium and Heavy