

YEAR 2006


Location

Kowloon External Cordon(Kolwoon Urban Area Boundary)

Stations on Cordon/Screenline

4201, 5017, 5021, 5022, 5023, 5024, 5026, 5030, 6203, 6204 and 6214

1. TRAFFIC FLOW VARIATION AND GROWTH



2. TRAFFIC CHARACTERISTICS (BY DIRECTION)

Parameter	All - Day	Mon. - Fri.	Sat.	Sun.
SOUTH BOUND				
A.A.D.T.	310350	323600	331810	248180
R 12 / 24 - %	71.6	73.1	70.3	63.6
R 16 / 24 - %	86.9	87.9	85.5	82
AM Peak Hour	0800-0900	0800-0900	0800-0900	0900-1000
One-way flow at AM peak hour	24500	27750	24340	12150
T - % (AM)	-	20.2	-	-
PM Peak Hour	1800-1900	1800-1900	1800-1900	1800-1900
One-way flow at PM peak hour	19500	20530	19570	15880
T - % (PM)	-	15.8	-	-
Prop.of commercial vehicles - 16 hr.	-	20.8	-	-
NORTH BOUND				
A.A.D.T.	306400	318740	326990	249430
R 12 / 24 - %	64.6	65.8	64.3	57.3
R 16 / 24 - %	84.7	85.9	83	78.9
AM Peak Hour	0800-0900	0800-0900	0900-1000	0900-1000
One-way flow at AM peak hour	17100	19340	17520	9800
T - % (AM)	-	18.8	-	-
PM Peak Hour	1800-1900	1800-1900	1800-1900	1700-1800
One-way flow at PM peak hour	20570	22300	19900	14270
T - % (PM)	-	16.6	-	-
Prop.of commercial vehicles - 16 hr.	-	20	-	-

3. OTHER INFORMATION AND COMMENT

Kowloon External Cordon
Year 2006

4. Vehicle classification and occupancy - Monday to Friday

Time		Class of vehicle									
		Motor	Private	Taxi	Private	PLB	Goods veh.		Non	Fr. Bus	
		Cycle	Car		LB		Light	M & H	Fr. Bus	SD	DD
0700-0800	Pro	4.3	30.6	16.5	0.9	3.4	20.4	12.3	6.6	0.1	4.9
	Ocp	1.1	1.5	1.9	4.1	11.7	1.5	1.2	16.0	16.0	53.6
0800-0900 Peak Hour	Pro	4.2	40.9	14.0	1.0	3.0	17.7	10.6	4.7	0.1	3.9
	Ocp	1.1	1.3	1.9	5.0	12.3	1.5	1.3	18.4	14.3	60.2
0900-1000	Pro	2.7	34.7	14.1	0.8	2.6	23.9	14.6	2.5	0.1	4.1
	Ocp	1.1	1.3	1.7	2.6	10.7	1.6	1.3	15.2	8.0	34.9
1000-1100	Pro	2.1	29.1	12.4	0.8	2.4	29.9	17.7	1.6	0.1	3.9
	Ocp	1.1	1.4	1.8	2.5	9.2	1.5	1.3	10.7	7.2	27.3
1100-1200	Pro	1.9	28.4	10.1	1.1	2.6	33.2	16.8	2.1	0.1	3.8
	Ocp	1.1	1.4	1.9	2.4	8.2	1.6	1.3	7.6	8.3	27.8
1200-1300	Pro	2.1	31.5	10.6	1.3	2.9	29.0	15.9	2.9	0.1	3.8
	Ocp	1.1	1.4	1.9	4.2	7.7	1.5	1.3	13.5	11.9	27.5
1300-1400	Pro	2.0	28.1	9.9	0.9	2.9	32.4	16.8	2.8	0.1	4.1
	Ocp	1.1	1.5	2.0	2.9	8.8	1.6	1.2	9.9	7.8	28.8
1400-1500	Pro	2.1	31.4	10.0	1.2	2.5	29.2	17.8	2.2	0.1	3.8
	Ocp	1.1	1.4	2.0	2.5	8.6	1.5	1.3	9.4	8.6	28.3
1500-1600	Pro	2.3	30.9	10.7	1.1	2.3	29.9	16.4	2.6	0.1	3.7
	Ocp	1.1	1.5	1.8	3.1	9.1	1.5	1.3	12.8	6.8	28.1
1600-1700	Pro	2.5	32.9	12.5	1.4	2.3	27.6	13.6	3.2	0.1	4.0
	Ocp	1.1	1.5	1.8	3.5	10.7	1.6	1.2	8.5	8.0	32.9
1700-1800	Pro	3.3	36.1	11.0	1.2	2.7	24.8	13.0	3.5	0.1	4.5
	Ocp	1.1	1.4	1.8	2.8	12.2	1.6	1.2	14.2	13.7	42.2
1800-1900	Pro	4.1	45.4	11.4	0.8	3.6	18.5	8.8	3.3	0.1	4.0
	Ocp	1.1	1.4	1.9	4.2	14.2	1.5	1.1	18.7	13.8	60.4
1900-2000	Pro	3.1	51.2	11.3	0.5	4.4	14.1	8.4	2.9	0.1	4.1
	Ocp	1.1	1.5	2.1	2.0	12.2	1.5	1.1	17.2	9.8	50.9
2000-2100	Pro	3.3	47.8	16.4	0.6	4.4	11.8	8.9	2.1	0.1	4.9
	Ocp	1.1	1.4	1.8	2.6	10.4	1.5	1.1	11.5	8.6	38.0
2100-2200	Pro	3.7	45.7	19.6	0.3	4.6	10.5	8.3	1.9	0.1	5.3
	Ocp	1.2	1.5	1.9	2.3	10.8	1.5	1.1	12.5	8.2	33.6
2200-2300	Pro	3.0	49.6	21.8	0.4	5.2	7.4	5.5	1.9	0.1	5.3
	Ocp	1.1	1.6	1.9	2.6	10.4	1.4	1.1	11.0	6.5	35.4
16 hours	Pro	3.0	36.9	13.0	0.9	3.1	22.9	13.0	3.0	0.1	4.2
	Ocp	1.1	1.4	1.9	3.3	10.8	1.5	1.2	14.1	9.9	39.3

Legend

- Pro.** Proportion of vehicles in % (Sum may not add up to 100% due to figure rounding)
- Ocp.** Average occupancy of vehicles
- M & H** Medium and Heavy