

YEAR 2008


Location

Screenline C-C(Kowloon Peninsula South of Dundas Street)

Stations on Cordon/Screenline

3001, 3006, 3014, 3024, 3025, 3026, 3103, 4205, 4209, 4210, 4211, 4212, 4213, 4214, 4215, 4220, 4401, 4403 and 4404

## 1. TRAFFIC FLOW VARIATION AND GROWTH



## 2. TRAFFIC CHARACTERISTICS (BY DIRECTION)

Parameter	All - Day	Mon. - Fri.	Sat.	Sun.
<b>SOUTH BOUND</b>				
A.A.D.T.	288790	294740	308570	252210
R 12 / 24 - %	65.2	66.5	63.4	60
R 16 / 24 - %	83.5	84.7	80.9	79.2
AM Peak Hour	0900-1000	0900-1000	0900-1000	0900-1000
One-way flow at AM peak hour	17390	18720	17830	11080
T - % (AM)	-	12.7	-	-
PM Peak Hour	1800-1900	1800-1900	1800-1900	1800-1900
One-way flow at PM peak hour	17780	18630	17040	15060
T - % (PM)	-	8.4	-	-
Prop.of commercial vehicles - 16 hr.	-	11.2	-	-
<b>NORTH BOUND</b>				
A.A.D.T.	285910	290680	304720	256150
R 12 / 24 - %	61.5	63	59.1	55.9
R 16 / 24 - %	81.6	83.2	78.1	76.5
AM Peak Hour	0900-1000	0800-0900	0900-1000	0900-1000
One-way flow at AM peak hour	13830	15080	14290	9870
T - % (AM)	-	14.9	-	-
PM Peak Hour	1800-1900	1800-1900	1700-1800	1800-1900
One-way flow at PM peak hour	17140	18000	16940	14330
T - % (PM)	-	10.1	-	-
Prop.of commercial vehicles - 16 hr.	-	11.7	-	-

## 3. OTHER INFORMATION AND COMMENT

**4. Vehicle classification and occupancy - Monday to Friday**

Time		Class of vehicle									
		Motor	Private	Taxi	Private	PLB	Goods veh.		Non	Fr. Bus	
		Cycle	Car		LB		Light	M & H	Fr. Bus	SD	DD
0700-0800	Pro	4.1	18.8	32.9	2.7	5.3	17.8	4.7	6.5	0.2	7.2
	Ocp	1.1	1.4	2.0	6.9	10.2	1.5	1.2	10.9	9.8	29.4
0800-0900	Pro	3.4	38.4	23.7	1.4	4.3	14.9	3.9	4.8	0.2	5.2
	Ocp	1.1	1.4	1.9	4.7	11.9	1.6	1.4	21.1	7.3	38.4
0900-1000	Pro	2.8	30.7	26.6	1.2	3.6	21.9	4.9	2.9	0.1	5.3
	Ocp	1.1	1.4	1.9	2.9	8.7	1.6	1.5	12.6	6.7	22.6
1000-1100	Pro	2.9	27.3	24.7	1.1	3.4	28.2	5.4	2.0	0.1	5.1
	Ocp	1.1	1.4	1.9	2.7	7.0	1.6	1.6	12.9	8.4	18.7
1100-1200	Pro	2.8	28.3	25.0	1.5	3.2	27.1	5.2	2.5	0.1	4.4
	Ocp	1.0	1.5	1.9	2.7	6.9	1.6	1.4	11.3	8.1	20.3
1200-1300	Pro	2.6	30.2	26.2	1.3	3.5	23.9	4.7	3.4	0.1	4.2
	Ocp	1.1	1.5	1.9	4.0	6.6	1.6	1.5	11.3	7.8	19.6
1300-1400	Pro	3.2	28.8	25.2	1.0	3.0	26.2	5.4	2.5	0.1	4.6
	Ocp	1.1	1.5	1.9	3.7	8.5	1.6	1.5	10.0	8.1	20.5
1400-1500	Pro	3.0	31.6	23.7	1.2	3.0	26.0	5.1	2.1	0.1	4.1
	Ocp	1.1	1.6	2.0	2.4	7.4	1.6	1.4	11.4	6.8	21.1
1500-1600	Pro	2.7	31.8	25.2	1.4	2.6	24.3	4.5	3.3	0.1	4.2
	Ocp	1.1	1.5	2.0	3.2	8.9	1.6	1.4	11.5	9.2	21.4
1600-1700	Pro	3.5	32.7	25.2	1.6	3.0	21.9	4.1	3.1	0.1	4.7
	Ocp	1.1	1.6	1.9	3.7	9.4	1.6	1.4	11.2	10.0	23.7
1700-1800	Pro	4.0	35.1	25.2	1.4	3.7	19.8	2.9	2.6	0.1	5.3
	Ocp	1.1	1.6	1.9	2.9	9.6	1.6	1.4	10.6	9.7	29.0
1800-1900	Pro	5.2	42.8	25.1	0.6	4.5	12.4	1.4	3.0	0.1	4.8
	Ocp	1.1	1.5	2.0	2.7	12.3	1.6	1.3	21.4	15.7	41.9
1900-2000	Pro	3.9	46.6	28.2	0.4	4.4	8.8	1.3	2.1	0.1	4.3
	Ocp	1.2	1.5	2.0	2.3	11.6	1.6	1.4	21.0	12.2	36.5
2000-2100	Pro	3.2	40.5	35.4	0.3	5.3	7.0	1.3	2.0	0.1	4.8
	Ocp	1.1	1.5	1.9	2.2	9.5	1.5	1.4	13.3	9.1	25.5
2100-2200	Pro	3.5	36.8	38.8	0.4	5.1	6.1	1.6	2.2	0.1	5.6
	Ocp	1.1	1.6	1.9	2.9	9.4	1.6	1.4	8.7	9.1	24.6
2200-2300	Pro	3.4	37.9	40.6	0.3	5.4	4.4	1.0	1.4	0.1	5.5
	Ocp	1.2	1.7	1.9	1.6	9.8	1.6	1.2	9.0	4.7	24.4
16 hours	Pro	3.4	33.9	27.8	1.1	3.9	18.5	3.6	2.9	0.1	4.9
	Ocp	1.1	1.5	1.9	3.6	9.5	1.6	1.4	13.6	8.9	26.5

**Legend**

- Pro.** Proportion of vehicles in % (Sum may not add up to 100% due to figure rounding)
- Ocp.** Average occupancy of vehicles
- M & H** Medium and Heavy