


YEAR 2008

Location Hong Kong External Cordon(Boundary between the Northern Part and Southern Part of Hong Kong Island)

Stations on Cordon/Screenline

1004, 1021, 2201, 2202, 2206, 2401 and 2407

1. TRAFFIC FLOW VARIATION AND GROWTH



2. TRAFFIC CHARACTERISTICS (BY DIRECTION)

Parameter	All - Day	Mon. - Fri.	Sat.	Sun.
SOUTH BOUND				
A.A.D.T.	65530	66840	68430	59100
R 12 / 24 - %	68.7	69.4	68	65.1
R 16 / 24 - %	87.5	88.4	85.6	84.2
AM Peak Hour	0900-1000	0900-1000	0900-1000	0900-1000
One-way flow at AM peak hour	3920	4200	3900	2750
T - % (AM)	-	11.8	-	-
PM Peak Hour	1600-1700	1800-1900	1600-1700	1600-1700
One-way flow at PM peak hour	3880	3970	4220	3610
T - % (PM)	-	8.2	-	-
Prop.of commercial vehicles - 16 hr.	-	11.6	-	-
NORTH BOUND				
A.A.D.T.	78740	81070	81570	67980
R 12 / 24 - %	73.1	74.3	71.3	68
R 16 / 24 - %	89.3	90.2	87.4	86
AM Peak Hour	0800-0900	0800-0900	0900-1000	0900-1000
One-way flow at AM peak hour	5630	6610	4950	3320
T - % (AM)	-	9.4	-	-
PM Peak Hour	1700-1800	1700-1800	1700-1800	1800-1900
One-way flow at PM peak hour	5090	5240	5270	4780
T - % (PM)	-	12.5	-	-
Prop.of commercial vehicles - 16 hr.	-	11.1	-	-

3. OTHER INFORMATION AND COMMENT

Hong Kong External Cordon Year 2008

4. Vehicle classification and occupancy - Monday to Friday

Time		Class of vehicle									
		Motor	Private	Taxi	Private	PLB	Goods veh.		Non	Fr. Bus	
		Cycle	Car		LB		Light	M & H	Fr. Bus	SD	DD
0700-0800	Pro	3.7	32.1	29.0	4.1	6.7	8.9	2.1	7.5	0.6	5.3
	Ocp	1.1	1.5	2.0	6.9	12.6	1.7	1.3	23.1	19.3	51.2
0800-0900 Peak Hour	Pro	3.1	49.7	20.8	1.7	5.0	9.4	1.6	4.2	0.3	4.1
	Ocp	1.1	1.4	1.9	5.1	14.7	1.8	1.4	13.5	21.3	59.2
0900-1000	Pro	2.5	41.6	22.3	1.4	5.8	16.0	3.2	2.1	0.4	4.7
	Ocp	1.2	1.4	2.0	3.7	12.9	1.8	1.4	12.3	15.4	32.0
1000-1100	Pro	2.1	35.4	21.4	1.3	4.9	22.9	4.5	2.2	0.5	4.9
	Ocp	1.0	1.4	1.9	2.6	10.0	1.6	1.5	14.2	8.7	19.6
1100-1200	Pro	1.7	35.8	19.3	1.8	5.2	23.2	4.0	3.8	0.5	4.7
	Ocp	1.0	1.4	2.1	2.9	10.1	1.7	1.5	9.1	10.6	21.8
1200-1300	Pro	2.5	37.8	21.2	2.4	5.3	18.2	3.9	3.8	0.4	4.4
	Ocp	1.1	1.5	2.0	5.0	10.6	1.6	1.5	14.5	8.8	22.6
1300-1400	Pro	2.2	33.4	23.8	1.6	5.0	21.3	4.0	3.9	0.5	4.5
	Ocp	1.0	1.5	2.0	3.8	10.6	1.6	1.4	13.3	11.1	21.3
1400-1500	Pro	2.0	36.2	22.6	1.5	5.0	21.0	3.6	3.5	0.4	4.1
	Ocp	1.1	1.5	1.9	2.5	9.7	1.7	1.6	6.4	9.5	19.6
1500-1600	Pro	2.4	41.4	20.1	2.5	4.8	16.1	3.8	4.4	0.5	4.0
	Ocp	1.1	1.7	2.1	5.0	10.5	1.7	1.5	16.1	11.3	23.6
1600-1700	Pro	2.5	40.3	20.9	2.3	5.2	15.9	2.9	5.0	0.4	4.6
	Ocp	1.1	1.6	1.9	4.0	11.7	1.7	1.5	7.9	12.5	28.5
1700-1800	Pro	4.3	43.3	19.5	1.8	6.2	12.9	1.8	4.9	0.4	5.0
	Ocp	1.1	1.6	2.2	3.8	12.4	1.9	1.5	16.4	18.1	40.9
1800-1900	Pro	4.5	46.8	24.5	0.8	5.4	8.3	0.8	3.9	0.4	4.5
	Ocp	1.2	1.5	2.1	3.5	15.2	1.8	1.7	19.0	21.5	56.5
1900-2000	Pro	2.5	47.7	30.8	0.4	5.5	5.3	0.6	1.9	0.4	4.9
	Ocp	1.1	1.5	2.0	2.5	11.9	1.6	1.7	14.8	13.9	42.0
2000-2100	Pro	3.4	46.1	33.5	0.4	6.1	2.4	0.7	0.9	0.5	6.0
	Ocp	1.2	1.6	1.8	5.2	10.5	1.4	1.3	9.0	9.0	25.6
2100-2200	Pro	2.9	40.8	36.6	0.4	7.4	3.5	0.7	1.1	0.5	6.1
	Ocp	1.1	1.6	1.8	2.2	9.9	1.5	1.6	6.5	8.5	22.3
2200-2300	Pro	2.7	39.4	39.2	0.4	7.8	3.1	0.3	0.6	0.4	6.1
	Ocp	1.1	1.7	1.9	1.8	9.5	1.8	1.4	8.0	5.4	22.6
16 hours	Pro	2.8	40.6	24.5	1.6	5.6	13.5	2.5	3.5	0.4	4.8
	Ocp	1.1	1.5	2.0	4.4	11.6	1.7	1.5	14.4	13.2	32.8

Legend

- Pro.** Proportion of vehicles in % (Sum may not add up to 100% due to figure rounding)
- Ocp.** Average occupancy of vehicles
- M & H** Medium and Heavy