

YEAR


2010

LINK






KO SHAN RD (from PAK KUNG ST to CHI KIANG ST)

CORE STATION
ROAD NETWORK
ROAD TYPE

3103
MINOR
LOCAL DISTRIBUTOR



1. TRAFFIC FLOW VARIATION AND GROWTH



2. TRAFFIC CHARACTERISTICS (BY DIRECTION)

Parameter	All - Day	Mon. - Fri.	Sat.	Sun.
SOUTH BOUND				
A.A.D.T.	3470	3500	3680	3180
R 12 / 24 - %	67.4	68	67.1	64.8
R 16 / 24 - %	87.2	87.8	86.3	85.1
AM Peak Hour	0800-0900	0800-0900	0900-1000	0900-1000
One-way flow at AM peak hour	190	210	190	170
T - % (AM)	-	-	-	-
PM Peak Hour	1700-1800	1700-1800	1700-1800	1700-1800
One-way flow at PM peak hour	210	210	230	190
T - % (PM)	-	3.4	-	-
Prop.of commercial vehicles - 16 hr.	-	2.2	-	-
NORTH BOUND				
A.A.D.T.	4100	4110	4380	3900
R 12 / 24 - %	69.3	69.8	68.7	67.7
R 16 / 24 - %	88.2	88.6	87.7	86.8
AM Peak Hour	0900-1000	0900-1000	0900-1000	0900-1000
One-way flow at AM peak hour	230	230	250	230
T - % (AM)	-	3.2	-	-
PM Peak Hour	1600-1700	1600-1700	1600-1700	1800-1900
One-way flow at PM peak hour	240	250	250	220
T - % (PM)	-	1.9	-	-
Prop.of commercial vehicles - 16 hr.	-	2.7	-	-

3. OTHER INFORMATION AND COMMENT

4. Vehicle classification and occupancy - Monday to Friday

Time		Class of vehicle									
		Motor	Private	Taxi	Private	PLB	Goods veh.		Non	Fr. Bus	
		Cycle	Car		LB		Light	M & H	Fr. Bus	SD	DD
0700-0800	Pro	0.0	7.7	50.8	9.2	10.8	9.2	0.0	12.3	0.0	0.0
	Ocp	0.0	1.2	2.3	4.0	5.0	1.7	0.0	19.0	0.0	0.0
0800-0900	Pro	4.0	34.3	33.3	5.1	9.1	11.1	1.0	2.0	0.0	0.0
	Ocp	1.0	1.6	1.8	6.0	10.4	1.3	1.0	6.0	0.0	0.0
0900-1000	Pro	2.5	20.8	48.3	1.7	10.8	12.5	1.7	1.7	0.0	0.0
	Ocp	1.0	1.2	1.5	3.0	5.5	1.7	1.5	12.0	0.0	0.0
1000-1100	Pro	1.1	23.2	53.7	0.0	6.3	12.6	1.1	2.1	0.0	0.0
	Ocp	1.0	1.3	1.2	0.0	5.2	1.7	2.0	14.5	0.0	0.0
1100-1200	Pro	2.7	20.9	47.3	1.8	9.1	16.4	0.0	1.8	0.0	0.0
	Ocp	1.0	1.5	1.1	4.5	5.6	1.9	0.0	1.0	0.0	0.0
1200-1300 Peak hour	Pro	2.5	19.7	50.0	1.6	5.7	14.8	0.0	5.7	0.0	0.0
	Ocp	1.0	1.6	1.3	5.0	5.1	1.6	0.0	7.0	0.0	0.0
1300-1400	Pro	1.4	25.2	46.0	4.3	5.8	15.8	0.0	1.4	0.0	0.0
	Ocp	1.0	1.5	1.5	3.2	7.0	1.5	0.0	7.5	0.0	0.0
1400-1500	Pro	1.8	23.0	51.3	0.0	9.7	14.2	0.0	0.0	0.0	0.0
	Ocp	1.0	1.3	1.3	0.0	6.4	1.9	0.0	0.0	0.0	0.0
1500-1600	Pro	2.9	16.7	52.0	1.0	8.8	17.6	0.0	1.0	0.0	0.0
	Ocp	1.0	1.5	1.6	2.0	7.1	1.6	0.0	1.0	0.0	0.0
1600-1700	Pro	0.0	25.5	47.1	0.0	7.8	17.6	1.0	1.0	0.0	0.0
	Ocp	0.0	1.5	1.4	0.0	5.1	1.6	2.0	5.0	0.0	0.0
1700-1800	Pro	1.9	29.0	35.5	2.8	10.3	16.8	0.9	2.8	0.0	0.0
	Ocp	1.0	1.6	1.6	2.3	9.6	1.4	2.0	18.0	0.0	0.0
1800-1900	Pro	5.9	41.2	22.6	1.0	12.7	14.7	1.0	1.0	0.0	0.0
	Ocp	1.0	1.6	2.4	1.0	13.8	1.6	1.0	2.0	0.0	0.0
1900-2000	Pro	18.4	29.8	37.7	0.0	6.1	6.1	1.8	0.0	0.0	0.0
	Ocp	1.0	1.6	1.8	0.0	11.4	1.6	1.5	0.0	0.0	0.0
2000-2100	Pro	6.3	22.5	52.5	0.0	8.8	10.0	0.0	0.0	0.0	0.0
	Ocp	1.2	1.7	1.5	0.0	10.1	1.9	0.0	0.0	0.0	0.0
2100-2200	Pro	2.5	35.0	41.3	0.0	13.8	7.5	0.0	0.0	0.0	0.0
	Ocp	1.0	1.5	1.3	0.0	5.6	2.0	0.0	0.0	0.0	0.0
2200-2300	Pro	2.1	30.9	51.1	1.1	14.9	0.0	0.0	0.0	0.0	0.0
	Ocp	1.5	1.8	1.6	5.0	5.0	0.0	0.0	0.0	0.0	0.0
16 hours	Pro	3.6	25.5	44.9	1.8	9.2	12.7	0.5	1.9	0.0	0.0
	Ocp	1.0	1.5	1.5	3.9	7.4	1.7	1.6	11.1	0.0	0.0

Legend

- Pro.** Proportion of vehicles in % (Sum may not add up to 100% due to figure rounding)
- Ocp.** Average occupancy of vehicles
- M&H** Medium and Heavy