


YEAR 2010

CORE STATION 1103






ROAD NETWORK MINOR

ROAD TYPE LOCAL DISTRIBUTOR

LINK STANLEY VILLAGE RD (from TAI TAM RD to STANLEY NEW ST)



1. TRAFFIC FLOW VARIATION AND GROWTH



2. TRAFFIC CHARACTERISTICS (BY DIRECTION)

Parameter	All - Day	Mon. - Fri.	Sat.	Sun.
SOUTH BOUND				
A.A.D.T.	6070	6020	6320	6100
R 12 / 24 - %	76.1	76.3	75.4	76.4
R 16 / 24 - %	91.4	91.9	90.3	90.6
AM Peak Hour	0900-1000	0700-0800	0900-1000	0900-1000
One-way flow at AM peak hour	370	400	370	360
T - % (AM)	-	-	-	-
PM Peak Hour	1700-1800	1600-1700	1700-1800	1600-1700
One-way flow at PM peak hour	430	420	460	480
T - % (PM)	-	-	-	-
Prop.of commercial vehicles - 16 hr.	-	-	-	-
NORTH BOUND				
A.A.D.T.	5810	5800	6010	5710
R 12 / 24 - %	79.8	80.8	77.6	77
R 16 / 24 - %	92.5	92.8	91.9	91.6
AM Peak Hour	0800-0900	0800-0900	0900-1000	0900-1000
One-way flow at AM peak hour	370	420	340	280
T - % (AM)	-	-	-	-
PM Peak Hour	1700-1800	1700-1800	1700-1800	1700-1800
One-way flow at PM peak hour	480	480	460	490
T - % (PM)	-	-	-	-
Prop.of commercial vehicles - 16 hr.	-	-	-	-

3. OTHER INFORMATION AND COMMENT