


YEAR 2014

CORE STATION 5026






ROAD NETWORK MAJOR

ROAD TYPE EXPRESSWAY

LINK TSING KWAI HIGHWAY (from CHING LAI COURT SLIP
RDS TO & FROM CHING CHEUNG RD to CHO YIU
CHUEN SLIP RDS TO & FROM KWAI CHUNG RD &
TSUEN WAN RD)



1. TRAFFIC FLOW VARIATION AND GROWTH



2. TRAFFIC CHARACTERISTICS (BY DIRECTION)

Parameter	All - Day	Mon. - Fri.	Sat.	Sun.
SOUTH BOUND				
A.A.D.T.	55480	57760	58200	44640
R 12 / 24 - %	71.6	73.3	68.8	64.4
R 16 / 24 - %	87.1	88.2	84.7	83.1
AM Peak Hour	0800-0900	0800-0900	0900-1000	0900-1000
One-way flow at AM peak hour	4090	4720	3870	2170
T - % (AM)	-	21.7	-	-
PM Peak Hour	1800-1900	1800-1900	1800-1900	1700-1800
One-way flow at PM peak hour	3740	4000	3620	2850
T - % (PM)	-	15.7	-	-
Prop.of commercial vehicles - 16 hr.	-	21.1	-	-
NORTH BOUND				
A.A.D.T.	33630	33980	36230	31300
R 12 / 24 - %	61.3	62.4	59.9	57.2
R 16 / 24 - %	83.7	84.9	81.1	79.9
AM Peak Hour	0800-0900	0800-0900	0900-1000	0900-1000
One-way flow at AM peak hour	1860	2130	1520	1270
T - % (AM)	-	21.5	-	-
PM Peak Hour	1800-1900	1800-1900	1800-1900	1700-1800
One-way flow at PM peak hour	2270	2360	2360	1910
T - % (PM)	-	15.2	-	-
Prop.of commercial vehicles - 16 hr.	-	19.2	-	-

3. OTHER INFORMATION AND COMMENT

4. Vehicle classification and occupancy - Monday to Friday

Time		Class of vehicle									
		Motor	Private	Taxi	Private	PLB	Goods veh.		Non	Fr. Bus	
		Cycle	Car		LB		Light	M & H	Fr. Bus	SD	DD
0700-0800	Pro	3.6	35.8	21.1	1.3	0.0	17.2	13.7	4.1	0.1	3.2
	Ocp	1.1	1.3	2.4	7.2	0.0	1.4	1.2	20.6	36.0	72.1
0800-0900	Pro	3.2	44.5	12.9	0.5	0.0	17.3	13.0	4.4	0.1	4.2
	Ocp	1.1	1.4	2.2	7.1	0.0	1.5	1.2	23.3	19.3	67.7
0900-1000	Pro	1.6	39.5	14.4	0.4	0.0	24.0	14.8	2.3	0.1	3.0
	Ocp	1.1	1.3	1.7	2.3	0.0	1.4	1.3	11.6	14.5	35.1
1000-1100	Pro	1.7	31.4	15.1	0.3	0.0	27.5	18.8	2.3	0.1	2.9
	Ocp	1.1	1.4	2.1	1.0	0.0	1.4	1.2	13.5	19.0	29.3
1100-1200	Pro	1.7	33.2	13.5	0.6	0.0	27.0	18.3	2.8	0.1	2.9
	Ocp	1.1	1.3	1.7	2.7	0.0	1.4	1.2	16.5	1.0	30.5
1200-1300	Pro	1.5	37.4	13.0	0.6	0.0	22.8	18.3	3.6	0.1	2.9
	Ocp	1.0	1.4	2.2	4.1	0.0	1.3	1.2	17.4	15.3	29.4
1300-1400	Pro	1.3	34.0	12.6	1.0	0.0	27.7	18.1	2.3	0.0	2.9
	Ocp	1.0	1.4	2.3	1.9	0.0	1.4	1.2	8.1	0.0	34.7
1400-1500	Pro	1.7	33.9	13.9	0.7	0.0	28.4	16.6	2.3	0.0	2.5
	Ocp	1.1	1.5	2.4	2.3	0.0	1.4	1.2	12.9	0.0	32.7
1500-1600	Pro	1.3	35.4	13.7	1.4	0.0	24.7	17.8	3.3	0.0	2.5
	Ocp	1.1	1.4	2.3	3.6	0.0	1.4	1.2	13.1	0.0	31.4
1600-1700	Pro	1.4	36.9	13.6	1.3	0.0	23.6	16.3	3.8	0.1	3.0
	Ocp	1.0	1.4	2.6	3.1	0.0	1.4	1.2	11.8	27.0	38.2
1700-1800	Pro	3.0	43.4	13.3	0.6	0.0	21.5	12.0	2.8	0.1	3.4
	Ocp	1.1	1.4	2.1	3.0	0.0	1.4	1.2	15.8	24.0	45.5
1800-1900	Pro	3.8	56.0	9.7	0.2	0.0	14.9	8.9	3.1	0.1	3.3
	Ocp	1.1	1.3	2.1	1.0	0.0	1.2	1.1	16.5	17.4	66.2
1900-2000	Pro	2.3	59.5	13.4	0.1	0.0	10.3	6.4	3.8	0.1	4.2
	Ocp	1.0	1.4	2.2	3.0	0.0	1.2	1.1	16.7	12.0	51.7
2000-2100	Pro	2.3	51.7	19.0	0.3	0.0	9.1	5.6	6.6	0.1	5.2
	Ocp	1.1	1.4	2.0	1.0	0.0	1.3	1.2	10.4	11.5	37.2
2100-2200	Pro	2.5	51.4	22.6	0.3	0.0	8.6	6.5	3.8	0.1	4.2
	Ocp	1.0	1.4	2.1	1.0	0.0	1.2	1.1	6.8	16.7	37.6
2200-2300	Pro	3.0	51.8	29.0	0.1	0.0	4.1	5.7	1.7	0.1	4.5
	Ocp	1.1	1.4	2.0	1.0	0.0	1.2	1.0	5.4	17.0	37.3
16 hours	Pro	2.3	41.9	15.1	0.6	0.0	19.9	13.5	3.3	0.1	3.4
	Ocp	1.1	1.4	2.1	3.6	0.0	1.4	1.2	14.8	16.7	44.5

Legend

Pro. Proportion of vehicles in % (Sum may not add up to 100% due to figure rounding)
Ocp. Average occupancy of vehicles
M&H Medium and Heavy