

YEAR

2003

LINK CONTAINER PORT RD S (from N/O PMH INT to S/O PMH INT)

COVERAGE (B) STATION


6214

ROAD NETWORK





MAJOR

ROAD TYPE

LOCAL DISTRIBUTOR



1. TRAFFIC FLOW VARIATION AND GROWTH



2. TRAFFIC CHARACTERISTICS (BY DIRECTION)

Parameter	All - Day	Mon. - Fri.	Sat.	Sun.
SOUTH BOUND				
A.A.D.T.	11480	13080	12890	4580
R 12 / 24 - %	76.2	77.4	74.1	64.5
R 16 / 24 - %	90.9	91.8	90	80.6
AM Peak Hour	0900-1000	0900-1000	0900-1000	0800-0900
One-way flow at AM peak hour	760	890	870	220
T - % (AM)	-	61.1	-	-
PM Peak Hour	1600-1700	1800-1900	1600-1700	1800-1900
One-way flow at PM peak hour	790	930	860	290
T - % (PM)	-	64.4	-	-
Prop.of commercial vehicles - 16 hr.	-	57.4	-	-
NORTH BOUND				
A.A.D.T.	13600	15180	15850	6540
R 12 / 24 - %	76.9	78.3	74.2	66.9
R 16 / 24 - %	91	92.2	89.6	81.7
AM Peak Hour	0800-0900	0800-0900	0900-1000	0900-1000
One-way flow at AM peak hour	1060	1270	1160	360
T - % (AM)	-	56.1	-	-
PM Peak Hour	1600-1700	1600-1700	1700-1800	1600-1700
One-way flow at PM peak hour	870	1010	990	380
T - % (PM)	-	66.8	-	-
Prop.of commercial vehicles - 16 hr.	-	66.1	-	-

3. OTHER INFORMATION AND COMMENT

4. Vehicle classification and occupancy - Monday to Friday

Time		Class of vehicle									
		Motor	Private	Taxi	Private	PLB	Goods veh.		Non	Fr. Bus	
		Cycle	Car		LB		Light	M & H	Fr. Bus	SD	DD
0700-0800	Pro	2.4	6.2	18.2	0.6	0.9	15.9	54.7	1.2	0.0	0.0
	Ocp	1.0	1.3	2.0	5.5	8.3	1.2	1.1	15.8	0.0	0.0
0800-0900 Peak hour	Pro	2.1	9.5	18.5	0.8	0.5	16.7	50.4	1.5	0.0	0.0
	Ocp	1.0	1.2	1.8	1.0	14.5	1.4	1.2	18.7	0.0	0.0
0900-1000	Pro	0.9	9.5	4.6	0.2	0.7	24.5	58.8	0.9	0.0	0.0
	Ocp	1.0	1.2	1.8	1.0	8.7	1.4	1.2	3.8	0.0	0.0
1000-1100	Pro	1.0	4.0	6.1	0.4	0.4	24.1	64.0	0.0	0.0	0.0
	Ocp	1.0	1.3	1.6	1.0	5.5	1.4	1.2	0.0	0.0	0.0
1100-1200	Pro	1.9	7.7	3.1	0.2	0.4	30.4	56.3	0.0	0.0	0.0
	Ocp	1.0	1.5	1.9	7.0	9.5	1.4	1.2	0.0	0.0	0.0
1200-1300	Pro	1.6	13.3	7.8	0.0	0.0	16.2	61.0	0.0	0.0	0.0
	Ocp	1.0	1.6	1.8	0.0	0.0	1.2	1.2	0.0	0.0	0.0
1300-1400	Pro	2.3	8.3	4.2	0.0	0.8	22.4	62.0	0.0	0.0	0.0
	Ocp	1.0	1.7	1.9	0.0	8.7	1.4	1.1	0.0	0.0	0.0
1400-1500	Pro	1.6	7.5	7.9	0.0	0.7	16.1	66.2	0.0	0.0	0.0
	Ocp	1.0	1.3	1.9	0.0	11.0	1.4	1.2	0.0	0.0	0.0
1500-1600	Pro	1.0	9.6	3.9	0.5	0.0	24.2	60.4	0.3	0.0	0.0
	Ocp	1.0	1.7	1.9	8.0	0.0	1.2	1.2	30.0	0.0	0.0
1600-1700	Pro	1.3	7.1	4.9	0.2	0.4	24.1	61.6	0.4	0.0	0.0
	Ocp	1.0	1.5	1.4	11.0	8.0	1.2	1.0	1.0	0.0	0.0
1700-1800	Pro	0.3	10.3	6.6	0.0	0.7	13.6	67.8	0.7	0.0	0.0
	Ocp	1.0	1.5	1.6	0.0	12.5	1.1	1.1	5.0	0.0	0.0
1800-1900	Pro	2.5	8.3	6.8	0.0	0.0	15.8	65.8	0.8	0.0	0.0
	Ocp	1.4	1.4	1.8	0.0	0.0	1.1	1.1	1.0	0.0	0.0
1900-2000	Pro	2.5	14.2	11.1	0.0	0.8	8.9	61.6	0.8	0.0	0.0
	Ocp	1.0	1.3	1.7	0.0	7.7	1.2	1.0	8.3	0.0	0.0
2000-2100	Pro	0.4	9.1	14.4	0.0	0.4	4.5	70.5	0.8	0.0	0.0
	Ocp	1.0	1.6	1.5	0.0	9.0	1.2	1.0	1.0	0.0	0.0
2100-2200	Pro	2.0	11.7	15.6	0.5	0.5	2.0	66.3	1.5	0.0	0.0
	Ocp	1.0	1.5	2.2	3.0	16.0	2.0	1.1	4.7	0.0	0.0
2200-2300	Pro	1.1	6.7	15.6	2.2	0.0	7.2	67.2	0.0	0.0	0.0
	Ocp	1.0	1.5	1.6	2.5	0.0	1.1	1.0	0.0	0.0	0.0
16 hours	Pro	1.6	8.7	8.5	0.3	0.5	18.4	61.5	0.5	0.0	0.0
	Ocp	1.0	1.4	1.8	3.8	9.5	1.3	1.1	9.2	0.0	0.0

Legend

- Pro.** Proportion of vehicles in % (Sum may not add up to 100% due to figure rounding)
- Ocp.** Average occupancy of vehicles
- M&H** Medium and Heavy