

YEAR 2004

CORE STATION 1004


ROAD NETWORK MAJOR

ROAD TYPE URBAN TRUNK ROAD

LINK ABERDEEN TUNNEL (from TOLL PLAZA to NORTH PORTAL)



1. TRAFFIC FLOW VARIATION AND GROWTH



2. TRAFFIC CHARACTERISTICS (BY DIRECTION)

Parameter	All - Day	Mon. - Fri.	Sat.	Sun.
SOUTH BOUND				
A.A.D.T.	30020	30690	31540	26580
R 12 / 24 - %	65.5	66.7	64.5	60.4
R 16 / 24 - %	84.9	86.1	82.5	80.7
AM Peak Hour	0900-1000	0900-1000	0900-1000	0900-1000
One-way flow at AM peak hour	1780	1920	1800	1140
T - % (AM)	-	18.8	-	-
PM Peak Hour	1600-1700	1600-1700	1600-1700	1600-1700
One-way flow at PM peak hour	1690	1720	1760	1540
T - % (PM)	-	15.7	-	-
Prop.of commercial vehicles - 16 hr.	-	17.4	-	-
NORTH BOUND				
A.A.D.T.	27800	28400	29400	24460
R 12 / 24 - %	72.9	74.4	70.6	67.3
R 16 / 24 - %	88.1	88.9	86.7	85.4
AM Peak Hour	0800-0900	0800-0900	0900-1000	0900-1000
One-way flow at AM peak hour	1890	2100	1970	1230
T - % (AM)	-	13.3	-	-
PM Peak Hour	1600-1700	1600-1700	1800-1900	1800-1900
One-way flow at PM peak hour	1650	1710	1720	1710
T - % (PM)	-	19.5	-	-
Prop.of commercial vehicles - 16 hr.	-	16.8	-	-

3. OTHER INFORMATION AND COMMENT

4. Vehicle classification and occupancy - Monday to Friday

Time		Class of vehicle									
		Motor	Private	Taxi	Private	PLB	Goods veh.		Non	Fr. Bus	
		Cycle	Car		LB		Light	M & H	Fr. Bus	SD	DD
0700-0800	Pro	3.6	29.5	23.5	3.2	4.1	15.3	4.0	6.8	0.2	9.8
	Ocp	1.1	1.4	2.2	5.6	10.8	1.5	1.3	19.7	31.5	49.2
0800-0900 Peak hour	Pro	3.0	45.5	15.4	1.6	5.8	13.3	3.2	3.4	0.2	8.6
	Ocp	1.1	1.3	2.0	4.6	14.6	1.7	1.3	12.4	28.7	60.5
0900-1000	Pro	2.3	36.4	21.2	1.2	4.4	18.7	3.5	3.3	0.1	8.9
	Ocp	1.0	1.3	1.9	1.9	10.9	1.6	1.3	27.0	19.4	31.7
1000-1100	Pro	1.4	32.6	17.9	1.7	4.5	24.1	6.1	3.7	0.2	7.7
	Ocp	1.0	1.4	2.0	3.1	8.3	1.5	1.6	15.3	14.4	24.7
1100-1200	Pro	1.5	35.5	14.6	1.4	3.9	25.9	5.1	3.9	0.2	8.0
	Ocp	1.0	1.5	2.1	2.7	10.2	1.7	1.5	6.4	13.8	21.3
1200-1300	Pro	1.9	34.7	13.2	1.6	4.4	26.5	6.5	3.4	0.1	7.7
	Ocp	1.1	1.6	2.2	5.8	9.4	1.7	1.6	19.1	7.0	18.9
1300-1400	Pro	2.7	30.7	13.5	1.5	4.3	26.0	6.1	7.7	0.2	7.4
	Ocp	1.2	1.7	2.4	3.9	7.7	1.7	1.3	17.8	15.6	19.4
1400-1500	Pro	2.5	35.5	14.8	1.8	3.8	24.2	6.3	3.8	0.2	7.2
	Ocp	1.1	1.5	2.2	4.6	8.5	1.6	1.5	13.3	10.6	17.8
1500-1600	Pro	2.0	41.1	12.3	2.0	3.4	20.3	5.0	6.5	0.2	7.3
	Ocp	1.1	1.4	2.2	3.6	10.0	1.8	1.6	15.1	12.8	18.3
1600-1700	Pro	3.0	36.6	17.2	1.3	3.8	20.3	4.3	5.3	0.2	8.1
	Ocp	1.1	1.4	2.0	3.7	10.2	1.7	1.4	13.0	15.3	23.8
1700-1800	Pro	4.7	39.0	13.6	0.9	4.7	19.9	2.8	3.9	0.3	10.1
	Ocp	1.1	1.5	2.0	2.8	13.0	1.6	1.4	17.4	9.5	46.2
1800-1900	Pro	3.7	49.3	12.5	1.0	4.4	13.2	1.2	5.2	0.2	9.4
	Ocp	1.2	1.4	2.3	3.0	16.1	1.8	1.3	19.6	18.6	66.1
1900-2000	Pro	2.4	51.8	17.4	0.8	5.7	7.4	1.1	1.8	0.2	11.5
	Ocp	1.1	1.5	2.1	6.6	12.1	1.6	1.6	14.3	10.3	42.9
2000-2100	Pro	3.3	43.3	23.6	0.4	6.3	7.7	1.7	0.8	0.2	12.8
	Ocp	1.2	1.4	2.1	1.5	11.2	1.4	1.1	15.3	6.8	30.4
2100-2200	Pro	3.1	41.9	30.2	0.0	6.8	4.7	1.2	1.2	0.1	11.0
	Ocp	1.1	1.6	2.1	0.0	10.1	1.6	1.2	9.5	1.0	29.2
2200-2300	Pro	2.9	37.1	33.8	0.2	8.5	2.9	1.1	0.7	0.1	12.6
	Ocp	1.2	1.6	2.1	1.0	8.7	1.2	1.2	4.7	1.0	27.9
16 hours	Pro	2.7	38.6	17.7	1.4	4.7	17.7	3.9	4.0	0.2	9.0
	Ocp	1.1	1.4	2.1	4.1	10.9	1.7	1.4	16.2	15.1	34.5

Legend

- Pro.** Proportion of vehicles in % (Sum may not add up to 100% due to figure rounding)
- Ocp.** Average occupancy of vehicles
- M&H** Medium and Heavy