


YEAR 2004

CORE STATION 3024


ROAD NETWORK MAJOR

ROAD TYPE URBAN TRUNK ROAD

LINK WEST KOWLOON HIGHWAY (from SLIP RDS TO & FROM LIN CHEUNG RD to HING WAH ST W)



1. TRAFFIC FLOW VARIATION AND GROWTH



2. TRAFFIC CHARACTERISTICS (BY DIRECTION)

Parameter	All - Day	Mon. - Fri.	Sat.	Sun.
SOUTH BOUND				
A.A.D.T.	45760	48530	47920	33830
R 12 / 24 - %	73.9	75.3	72.8	65.5
R 16 / 24 - %	89.3	90.2	87.8	84.5
AM Peak Hour	0800-0900	0800-0900	0800-0900	0900-1000
One-way flow at AM peak hour	4260	4930	4120	1540
T - % (AM)	-	23.2	-	-
PM Peak Hour	1800-1900	1800-1900	1800-1900	1800-1900
One-way flow at PM peak hour	3140	3420	2810	2370
T - % (PM)	-	10.5	-	-
Prop.of commercial vehicles - 16 hr.	-	15.1	-	-
NORTH BOUND				
A.A.D.T.	28410	29600	29830	23570
R 12 / 24 - %	64.9	66.3	64.1	57.6
R 16 / 24 - %	85.2	86.5	82.7	79.9
AM Peak Hour	0800-0900	0800-0900	0900-1000	0900-1000
One-way flow at AM peak hour	1570	1810	1520	890
T - % (AM)	-	12.6	-	-
PM Peak Hour	1800-1900	1800-1900	1800-1900	1700-1800
One-way flow at PM peak hour	2010	2210	1800	1410
T - % (PM)	-	24.6	-	-
Prop.of commercial vehicles - 16 hr.	-	14.7	-	-

3. OTHER INFORMATION AND COMMENT

4. Vehicle classification and occupancy - Monday to Friday

Time		Class of vehicle									
		Motor	Private	Taxi	Private	PLB	Goods veh.		Non	Fr. Bus	
		Cycle	Car		LB		Light	M & H	Fr. Bus	SD	DD
0700-0800	Pro	2.7	37.8	21.3	0.3	0.0	17.1	6.9	7.2	0.1	6.6
	Ocp	1.1	1.4	2.1	2.5	0.0	1.2	1.1	11.4	8.5	44.3
0800-0900 Peak hour	Pro	2.1	49.8	15.0	0.3	0.0	12.8	6.2	9.0	0.0	4.8
	Ocp	1.1	1.3	1.9	1.3	0.0	1.5	1.4	32.7	0.0	52.0
0900-1000	Pro	1.7	47.1	12.9	1.1	0.0	22.3	7.7	2.9	0.0	4.2
	Ocp	1.1	1.4	2.0	9.1	0.0	1.6	1.4	16.7	0.0	31.3
1000-1100	Pro	1.4	40.1	16.5	1.5	0.0	26.3	8.1	2.3	0.1	3.9
	Ocp	1.2	1.5	2.0	2.3	0.0	1.8	1.4	8.3	19.0	27.2
1100-1200	Pro	1.0	47.5	12.5	0.7	0.0	22.8	7.8	4.0	0.1	3.6
	Ocp	1.0	1.5	2.2	2.3	0.0	1.4	1.3	12.8	9.0	25.0
1200-1300	Pro	1.2	48.3	13.1	1.2	0.0	21.3	6.5	4.3	0.0	4.2
	Ocp	1.0	1.4	2.1	1.7	0.0	1.6	1.3	11.5	0.0	29.0
1300-1400	Pro	1.1	45.6	13.6	1.5	0.0	22.2	8.2	3.6	0.1	4.2
	Ocp	1.1	1.4	2.5	3.4	0.0	1.6	1.4	11.9	8.0	32.5
1400-1500	Pro	1.2	44.6	14.2	0.9	0.0	24.8	6.7	3.7	0.0	3.9
	Ocp	1.0	1.9	2.5	2.3	0.0	1.6	1.4	6.5	0.0	27.8
1500-1600	Pro	1.1	47.3	11.2	1.3	0.0	25.4	6.2	3.6	0.0	3.9
	Ocp	1.1	1.8	2.1	1.8	0.0	1.8	1.5	9.5	0.0	27.1
1600-1700	Pro	1.7	48.9	11.3	1.0	0.0	21.6	7.6	3.5	0.0	4.4
	Ocp	1.2	1.5	1.8	2.4	0.0	1.8	1.4	7.4	0.0	34.5
1700-1800	Pro	2.2	53.8	10.0	1.4	0.0	19.5	4.4	3.9	0.0	4.8
	Ocp	1.1	1.4	1.9	2.3	0.0	1.6	1.3	6.6	0.0	42.4
1800-1900	Pro	2.2	57.7	9.1	1.4	0.0	12.7	2.9	9.4	0.0	4.6
	Ocp	1.1	1.4	2.4	5.3	0.0	1.5	1.4	31.1	0.0	50.3
1900-2000	Pro	1.6	65.6	12.4	0.6	0.0	8.6	2.1	4.4	0.1	4.6
	Ocp	1.1	1.4	2.1	1.2	0.0	1.5	1.3	21.4	24.0	48.5
2000-2100	Pro	1.2	66.0	12.9	0.5	0.0	7.6	2.2	4.4	0.0	5.1
	Ocp	1.2	1.5	2.4	1.0	0.0	1.7	1.5	17.9	0.0	37.8
2100-2200	Pro	1.0	61.7	17.8	0.6	0.0	6.6	1.8	4.2	0.1	6.2
	Ocp	1.0	1.7	2.0	3.5	0.0	1.6	1.2	11.5	24.0	36.4
2200-2300	Pro	2.1	64.5	17.7	0.6	0.0	4.0	1.8	3.4	0.1	5.8
	Ocp	1.4	1.7	2.1	3.0	0.0	1.4	1.1	10.3	13.0	33.7
16 hours	Pro	1.6	51.3	13.5	1.0	0.0	17.7	5.6	4.7	0.1	4.6
	Ocp	1.1	1.5	2.1	3.2	0.0	1.6	1.4	18.4	14.3	37.5

Legend

- Pro.** Proportion of vehicles in % (Sum may not add up to 100% due to figure rounding)
- Ocp.** Average occupancy of vehicles
- M&H** Medium and Heavy