

YEAR

2005

LINK FAN KAM RD (from KAM TIN RD to CASTLE PEAK RD)

COVERAGE (B) STATION


6212

ROAD NETWORK






MAJOR

ROAD TYPE

RURAL ROAD



1. TRAFFIC FLOW VARIATION AND GROWTH



2. TRAFFIC CHARACTERISTICS (BY DIRECTION)

Parameter	All - Day	Mon. - Fri.	Sat.	Sun.
SOUTH BOUND				
A.A.D.T.	5020	5340	5360	3580
R 12 / 24 - %	76.2	77.8	75	66.7
R 16 / 24 - %	90.7	91.7	90	84.7
AM Peak Hour	0900-1000	0900-1000	0900-1000	0900-1000
One-way flow at AM peak hour	310	340	320	180
T - % (AM)	-	16.6	-	-
PM Peak Hour	1800-1900	1800-1900	1700-1800	1800-1900
One-way flow at PM peak hour	370	400	400	230
T - % (PM)	-	4.5	-	-
Prop.of commercial vehicles - 16 hr.	-	11.8	-	-
NORTH BOUND				
A.A.D.T.	4980	5320	5280	3460
R 12 / 24 - %	74.5	75.8	74.6	63.9
R 16 / 24 - %	89.9	90.7	89.8	83.2
AM Peak Hour	0900-1000	0900-1000	0900-1000	0900-1000
One-way flow at AM peak hour	300	340	310	180
T - % (AM)	-	13.6	-	-
PM Peak Hour	1600-1700	1700-1800	1600-1700	1600-1700
One-way flow at PM peak hour	360	390	400	210
T - % (PM)	-	14.6	-	-
Prop.of commercial vehicles - 16 hr.	-	13.3	-	-

3. OTHER INFORMATION AND COMMENT

Coverage (B) Station 6212
Year 2005

4. Vehicle classification and occupancy - Monday to Friday

Time		Class of vehicle									
		Motor	Private	Taxi	Private	PLB	Goods veh.		Non	Fr. Bus	
		Cycle	Car		LB		Light	M & H	Fr. Bus	SD	DD
0700-0800	Pro	1.0	34.1	10.3	1.0	16.5	21.7	9.3	4.1	1.8	0.0
	Ocp	1.0	1.7	1.9	1.0	9.9	1.6	1.6	7.3	19.6	0.0
0800-0900	Pro	0.0	45.1	11.8	2.0	8.5	18.3	11.8	1.3	1.0	0.3
	Ocp	0.0	1.4	1.2	9.3	9.1	1.6	1.3	6.5	20.5	24.0
0900-1000	Pro	1.8	42.0	9.6	3.0	6.6	22.2	13.8	0.0	0.9	0.2
	Ocp	1.0	1.2	1.4	3.4	8.0	1.2	1.3	0.0	10.7	17.0
1000-1100	Pro	2.0	40.5	2.7	0.0	3.3	39.1	10.6	0.7	1.0	0.2
	Ocp	1.0	1.4	1.3	0.0	7.0	1.2	1.2	1.0	10.7	8.0
1100-1200	Pro	0.6	37.8	7.4	0.6	6.8	34.1	11.8	0.0	0.5	0.5
	Ocp	1.0	1.3	1.7	2.0	8.0	1.3	1.0	0.0	10.0	13.7
1200-1300	Pro	0.7	41.0	8.5	2.6	6.5	26.1	11.1	2.6	0.7	0.3
	Ocp	1.0	1.2	1.5	4.0	7.0	1.4	1.1	6.0	6.5	17.0
1300-1400	Pro	0.0	39.7	6.0	1.6	5.4	32.1	12.0	2.2	0.7	0.3
	Ocp	0.0	1.6	1.5	9.0	8.2	1.5	1.1	6.0	14.6	24.5
1400-1500	Pro	3.5	37.0	10.6	0.5	4.1	29.9	13.7	0.0	0.6	0.1
	Ocp	1.0	1.7	1.5	3.0	10.3	1.5	1.2	0.0	10.8	7.0
1500-1600 Peak hour	Pro	1.0	39.3	7.7	1.5	3.6	31.1	14.3	0.5	0.8	0.3
	Ocp	1.0	1.4	1.9	8.0	10.6	1.2	1.1	22.0	10.2	19.0
1600-1700	Pro	0.0	47.0	7.6	0.5	3.5	30.3	9.6	0.5	0.5	0.4
	Ocp	0.0	1.6	1.5	1.0	9.0	1.4	1.2	18.0	12.0	18.7
1700-1800	Pro	0.6	43.1	7.8	0.6	4.8	32.3	9.6	0.0	1.0	0.3
	Ocp	1.0	1.4	1.5	6.0	12.9	1.3	1.1	0.0	23.0	29.5
1800-1900	Pro	2.6	65.2	5.2	0.6	5.2	16.1	3.2	0.6	1.0	0.3
	Ocp	1.0	1.5	1.6	2.0	13.8	1.3	1.6	19.0	29.0	24.0
1900-2000	Pro	1.1	68.1	3.2	1.1	8.6	13.0	3.2	0.0	1.1	0.5
	Ocp	1.0	1.4	1.3	1.0	9.6	1.6	1.0	0.0	14.0	18.0
2000-2100	Pro	0.0	60.2	16.5	0.0	8.3	5.9	7.1	0.0	1.8	0.3
	Ocp	0.0	1.2	1.4	0.0	8.7	1.2	1.3	0.0	11.0	5.0
2100-2200	Pro	1.8	46.8	16.2	0.0	7.2	7.2	18.0	0.0	2.3	0.5
	Ocp	1.0	1.3	1.3	0.0	7.3	1.0	1.1	0.0	6.2	18.0
2200-2300	Pro	1.4	67.6	17.9	0.0	2.8	4.1	4.1	0.0	1.4	0.7
	Ocp	1.0	1.3	1.5	0.0	5.5	1.0	1.0	0.0	5.8	6.5
16 hours	Pro	1.1	45.3	8.5	1.1	5.9	25.5	10.5	0.8	0.9	0.3
	Ocp	1.0	1.4	1.5	5.1	9.3	1.4	1.2	8.3	14.2	17.7

Legend

Pro. Proportion of vehicles in % (Sum may not add up to 100% due to figure rounding)
Ocp. Average occupancy of vehicles
M&H Medium and Heavy