


YEAR 2009

COVERAGE (B) STATION 4214


ROAD NETWORK MAJOR

ROAD TYPE PRIMARY DISTRIBUTOR

LINK FERRY ST & FERRY ST <FO> (from WATERLOO RD to SHANTUNG ST)



1. TRAFFIC FLOW VARIATION AND GROWTH



2. TRAFFIC CHARACTERISTICS (BY DIRECTION)

Parameter	All - Day	Mon. - Fri.	Sat.	Sun.
SOUTH BOUND				
A.A.D.T.	42950	42400	43510	45580
R 12 / 24 - %	63.7	65	62	58.7
R 16 / 24 - %	80.6	82.7	79	72.6
AM Peak Hour	0900-1000	0800-0900	0900-1000	0900-1000
One-way flow at AM peak hour	2430	2530	2290	2650
T - % (AM)	-	6.2	-	-
PM Peak Hour	1800-1900	1800-1900	1800-1900	1800-1900
One-way flow at PM peak hour	2510	2650	2380	2010
T - % (PM)	-	2.4	-	-
Prop.of commercial vehicles - 16 hr.	-	5.2	-	-
NORTH BOUND				
A.A.D.T.	36490	37060	38090	32270
R 12 / 24 - %	63.1	65	61.4	54.3
R 16 / 24 - %	82.4	84.3	79.7	74.3
AM Peak Hour	0900-1000	0800-0900	0900-1000	0900-1000
One-way flow at AM peak hour	1810	2020	1720	1140
T - % (AM)	-	6.7	-	-
PM Peak Hour	1800-1900	1800-1900	1600-1700	1600-1700
One-way flow at PM peak hour	2180	2300	2200	1720
T - % (PM)	-	3.5	-	-
Prop.of commercial vehicles - 16 hr.	-	6	-	-

3. OTHER INFORMATION AND COMMENT

4. Vehicle classification and occupancy - Monday to Friday

Time		Class of vehicle									
		Motor	Private	Taxi	Private	PLB	Goods veh.		Non	Fr. Bus	
		Cycle	Car		LB		Light	M & H	Fr. Bus	SD	DD
0700-0800	Pro	7.5	20.6	25.8	0.6	6.1	27.5	7.1	3.8	0.0	0.9
	Ocp	1.0	1.4	1.9	2.3	12.5	1.5	1.2	12.6	0.0	3.6
0800-0900	Pro	5.7	33.6	24.2	0.5	7.3	22.2	3.6	2.5	0.0	0.3
	Ocp	1.0	1.4	2.0	2.8	13.1	1.6	1.4	9.4	0.0	12.1
0900-1000	Pro	5.6	27.1	21.7	0.6	6.1	32.7	3.8	1.9	0.0	0.5
	Ocp	1.1	1.4	1.8	2.4	12.5	1.7	1.6	7.0	0.0	1.0
1000-1100	Pro	5.3	22.9	18.2	1.1	4.9	40.6	5.8	0.8	0.0	0.4
	Ocp	1.1	1.5	2.0	2.4	8.8	1.6	1.5	8.5	0.0	1.0
1100-1200	Pro	5.5	26.3	16.9	1.4	3.5	39.0	6.2	0.9	0.0	0.3
	Ocp	1.1	1.5	1.9	5.5	9.0	1.6	1.5	4.0	0.0	1.0
1200-1300	Pro	5.1	27.8	17.3	1.1	2.9	39.6	5.2	0.9	0.0	0.1
	Ocp	1.1	1.4	2.1	2.5	9.1	1.5	1.6	10.3	0.0	1.0
1300-1400	Pro	5.5	27.8	17.4	0.9	4.0	38.4	4.7	1.3	0.0	0.1
	Ocp	1.1	1.5	1.9	3.1	7.5	1.6	1.5	7.5	0.0	1.0
1400-1500	Pro	6.4	27.4	16.1	1.2	3.0	39.8	5.0	1.0	0.0	0.1
	Ocp	1.1	1.4	2.2	3.1	9.1	1.6	1.6	4.8	0.0	1.0
1500-1600	Pro	5.4	30.0	20.0	0.8	3.7	34.9	4.0	1.0	0.0	0.3
	Ocp	1.0	1.5	2.0	1.9	8.8	1.6	1.7	12.8	0.0	1.0
1600-1700	Pro	5.5	31.5	20.7	1.0	3.3	31.6	3.9	2.1	0.1	0.5
	Ocp	1.1	1.5	2.0	3.7	11.7	1.6	1.6	8.5	1.0	1.0
1700-1800	Pro	7.9	31.5	23.3	0.9	4.1	27.7	3.0	1.0	0.0	0.5
	Ocp	1.0	1.4	2.0	1.8	13.8	1.7	1.5	2.1	0.0	1.0
1800-1900 Peak hour	Pro	8.6	42.2	21.4	0.4	7.2	17.4	1.4	1.3	0.0	0.2
	Ocp	1.1	1.5	2.0	2.2	15.0	1.6	1.2	10.3	0.0	1.0
1900-2000	Pro	6.2	44.6	25.6	0.2	8.5	11.3	1.8	1.3	0.0	0.5
	Ocp	1.1	1.5	2.0	1.0	12.9	1.6	1.6	14.7	0.0	1.0
2000-2100	Pro	4.4	38.5	35.1	0.2	8.5	10.1	0.8	2.0	0.0	0.4
	Ocp	1.1	1.6	1.9	2.5	12.3	1.6	1.5	8.3	0.0	1.0
2100-2200	Pro	4.3	37.1	35.7	0.1	9.4	8.9	1.7	2.4	0.0	0.4
	Ocp	1.2	1.6	2.0	1.0	9.9	1.6	1.8	7.4	0.0	1.0
2200-2300	Pro	3.8	35.6	41.4	0.3	8.6	7.5	1.6	0.3	0.1	1.0
	Ocp	1.3	1.6	2.0	3.3	12.2	1.5	1.6	17.7	1.0	1.0
16 hours	Pro	5.8	31.8	23.3	0.7	5.6	27.1	3.7	1.5	0.1	0.4
	Ocp	1.1	1.5	2.0	2.9	11.7	1.6	1.5	9.0	1.0	1.9

Legend

Pro. Proportion of vehicles in % (Sum may not add up to 100% due to figure rounding)
Ocp. Average occupancy of vehicles
M&H Medium and Heavy