


YEAR 2009

CORE STATION 3025






ROAD NETWORK MAJOR

ROAD TYPE URBAN TRUNK ROAD

LINK LIN CHEUNG RD (from YAU MA TEI INT to CHERRY ST UNDERPASS)



1. TRAFFIC FLOW VARIATION AND GROWTH



2. TRAFFIC CHARACTERISTICS (BY DIRECTION)

Parameter	All - Day	Mon. - Fri.	Sat.	Sun.
NORTH BOUND				
A.A.D.T.	13280	14000	13430	10560
R 12 / 24 - %	60	63.1	49.4	53.2
R 16 / 24 - %	79.2	82.8	64.1	74.4
AM Peak Hour	0900-1000	0800-0900	0900-1000	0900-1000
One-way flow at AM peak hour	680	760	580	450
T - % (AM)	-	19.4	-	-
PM Peak Hour	1700-1800	1700-1800	1700-1800	1700-1800
One-way flow at PM peak hour	850	950	710	550
T - % (PM)	-	11.4	-	-
Prop.of commercial vehicles - 16 hr.	-	15.8	-	-
 A.A.D.T.	-	-	-	-
R 12 / 24 - %	-	-	-	-
R 16 / 24 - %	-	-	-	-
AM Peak Hour	-	-	-	-
One-way flow at AM peak hour	-	-	-	-
T - % (AM)	-	-	-	-
PM Peak Hour	-	-	-	-
One-way flow at PM peak hour	-	-	-	-
T - % (PM)	-	-	-	-
Prop.of commercial vehicles - 16 hr.	-	-	-	-

3. OTHER INFORMATION AND COMMENT

4. Vehicle classification and occupancy - Monday to Friday

Time		Class of vehicle									
		Motor	Private	Taxi	Private	PLB	Goods veh.		Non	Fr. Bus	
		Cycle	Car		LB		Light	M & H	Fr. Bus	SD	DD
0700-0800	Pro	4.5	25.2	28.5	0.6	0.0	19.6	9.0	9.5	0.0	3.2
	Ocp	1.1	1.2	2.0	4.0	0.0	1.4	1.1	4.2	0.0	21.1
0800-0900	Pro	2.5	35.1	27.0	2.1	0.4	13.5	6.7	10.3	0.1	2.3
	Ocp	1.0	1.4	1.7	7.0	1.0	1.2	1.2	4.1	1.0	35.2
0900-1000	Pro	1.6	32.7	24.8	0.4	0.0	18.8	8.8	8.8	0.0	4.2
	Ocp	1.0	1.2	1.8	1.0	0.0	1.3	1.1	6.0	0.0	11.3
1000-1100	Pro	1.0	31.6	18.2	1.0	1.0	24.9	10.4	7.3	0.0	4.5
	Ocp	1.0	1.4	2.0	8.5	1.0	1.3	1.2	8.6	0.0	8.1
1100-1200	Pro	2.6	31.6	16.3	1.5	1.0	27.6	11.2	5.1	0.0	3.1
	Ocp	1.4	1.5	2.0	1.0	1.0	1.4	1.1	4.9	0.0	11.7
1200-1300	Pro	0.8	28.0	20.2	2.9	1.2	25.2	12.4	7.8	0.0	1.4
	Ocp	1.0	1.6	1.8	2.6	1.0	1.6	1.1	11.4	0.0	20.4
1300-1400	Pro	1.4	29.7	25.5	1.4	0.5	24.5	12.3	3.3	0.0	1.4
	Ocp	1.0	1.5	2.4	4.3	1.0	1.2	1.2	1.7	0.0	25.4
1400-1500	Pro	2.9	39.6	17.1	1.0	0.0	23.0	9.3	5.9	0.0	1.2
	Ocp	1.2	1.4	1.9	1.5	0.0	1.3	1.1	13.3	0.0	31.0
1500-1600	Pro	0.8	35.5	21.3	2.5	0.4	22.1	11.7	4.6	0.0	1.1
	Ocp	1.0	1.6	2.4	1.8	1.0	1.3	1.2	6.5	0.0	13.9
1600-1700	Pro	1.3	25.1	28.1	1.7	0.0	26.8	6.0	9.9	0.0	1.2
	Ocp	1.0	1.8	1.9	1.0	0.0	1.4	1.1	1.6	0.0	35.0
1700-1800 Peak hour	Pro	5.4	42.9	21.8	1.1	0.0	17.5	3.2	6.1	0.0	2.1
	Ocp	1.1	1.3	2.0	1.7	0.0	1.2	1.0	9.6	0.0	34.3
1800-1900	Pro	3.7	44.6	18.2	1.7	0.0	23.3	3.4	3.0	0.0	2.0
	Ocp	1.1	2.2	2.1	1.0	0.0	1.2	1.1	8.0	0.0	58.9
1900-2000	Pro	2.6	50.7	26.0	0.7	0.3	8.8	3.9	5.5	0.0	1.5
	Ocp	1.3	1.5	2.0	1.0	1.0	1.1	1.1	12.7	0.0	41.1
2000-2100	Pro	2.3	45.9	25.9	0.4	0.0	9.3	3.9	8.9	0.1	3.4
	Ocp	1.2	1.5	2.2	12.0	0.0	1.1	1.0	10.2	1.0	12.4
2100-2200	Pro	2.1	49.5	28.7	0.0	1.1	6.9	5.3	4.8	0.0	1.6
	Ocp	1.0	1.4	1.9	0.0	1.0	1.1	1.1	4.6	0.0	9.2
2200-2300	Pro	3.5	40.0	45.9	0.4	0.4	3.5	0.8	4.3	0.0	1.2
	Ocp	1.1	1.3	2.1	1.0	1.0	1.0	1.0	7.7	0.0	20.5
16 hours	Pro	2.5	37.2	24.8	1.2	0.4	18.2	7.0	6.6	0.1	2.2
	Ocp	1.1	1.5	2.0	3.0	1.0	1.3	1.1	7.1	1.0	23.0

Legend

- Pro.** Proportion of vehicles in % (Sum may not add up to 100% due to figure rounding)
- Ocp.** Average occupancy of vehicles
- M&H** Medium and Heavy