


YEAR 2009

COVERAGE (B) STATION 4207


ROAD NETWORK MAJOR

ROAD TYPE DISTRICT DISTRIBUTOR

LINK CHEONG WAN RD & GILLIES AVE S (from RAILWAY TERMINUS to WUHU ST)



1. TRAFFIC FLOW VARIATION AND GROWTH



2. TRAFFIC CHARACTERISTICS (BY DIRECTION)

Parameter	All - Day	Mon. - Fri.	Sat.	Sun.
SOUTH BOUND				
A.A.D.T.	8460	8780	9480	6300
R 12 / 24 - %	69.4	70.9	67.1	61.9
R 16 / 24 - %	88.7	89.8	87.3	82.9
AM Peak Hour	0900-1000	0800-0900	0900-1000	0900-1000
One-way flow at AM peak hour	500	560	530	290
T - % (AM)	-	12.8	-	-
PM Peak Hour	1800-1900	1700-1800	1800-1900	1800-1900
One-way flow at PM peak hour	610	650	660	420
T - % (PM)	-	10	-	-
Prop.of commercial vehicles - 16 hr.	-	9.6	-	-
NORTH BOUND				
A.A.D.T.	9880	9940	10480	9540
R 12 / 24 - %	64	64.5	62.6	63.1
R 16 / 24 - %	84.4	85	83.1	82.6
AM Peak Hour	0800-0900	0800-0900	0900-1000	0900-1000
One-way flow at AM peak hour	590	650	640	480
T - % (AM)	-	11.4	-	-
PM Peak Hour	1800-1900	1800-1900	1800-1900	1800-1900
One-way flow at PM peak hour	580	590	570	580
T - % (PM)	-	2.7	-	-
Prop.of commercial vehicles - 16 hr.	-	5.4	-	-

3. OTHER INFORMATION AND COMMENT

4. Vehicle classification and occupancy - Monday to Friday

Time		Class of vehicle									
		Motor	Private	Taxi	Private	PLB	Goods veh.		Non	Fr. Bus	
		Cycle	Car		LB		Light	M & H	Fr. Bus	SD	DD
0700-0800	Pro	1.5	4.9	56.3	0.0	17.8	11.4	0.0	3.5	0.0	4.7
	Ocp	1.3	1.5	1.6	0.0	15.0	1.5	0.0	9.0	0.0	25.5
0800-0900	Pro	0.0	11.0	55.2	0.3	14.0	7.5	0.3	7.5	0.0	4.2
	Ocp	0.0	1.7	1.9	4.0	16.4	1.3	1.0	8.0	0.0	29.6
0900-1000	Pro	1.3	13.1	55.9	0.6	12.2	8.1	0.6	4.4	0.0	3.8
	Ocp	1.0	1.5	1.9	3.5	15.6	1.7	1.0	6.9	0.0	23.2
1000-1100	Pro	0.4	8.8	51.5	1.5	14.9	16.4	0.8	2.3	0.0	3.5
	Ocp	1.0	1.3	1.8	2.5	12.6	1.6	1.5	3.2	0.0	15.4
1100-1200	Pro	0.4	18.0	47.8	0.4	14.7	12.7	0.8	2.0	0.0	3.3
	Ocp	1.0	1.4	1.8	1.0	12.1	1.6	1.5	5.4	0.0	18.2
1200-1300	Pro	1.6	13.8	48.2	1.2	13.8	15.0	0.8	2.4	0.1	3.1
	Ocp	1.0	1.3	1.8	1.7	13.6	1.8	1.5	14.0	8.0	19.4
1300-1400	Pro	0.4	11.7	51.1	0.8	15.1	12.1	2.1	3.4	0.0	3.2
	Ocp	1.0	1.6	1.8	1.5	11.0	1.7	1.2	9.5	0.0	19.8
1400-1500	Pro	0.5	14.2	45.9	0.0	14.7	19.3	0.9	0.9	0.0	3.7
	Ocp	1.0	1.7	1.8	0.0	13.5	1.7	2.0	5.0	0.0	19.4
1500-1600	Pro	1.9	14.8	47.8	0.4	12.0	14.4	2.7	2.3	0.0	3.7
	Ocp	1.0	1.7	1.8	2.0	14.4	1.5	1.3	7.2	0.0	16.1
1600-1700	Pro	1.6	15.8	48.9	0.4	12.6	14.6	0.8	2.0	0.0	3.4
	Ocp	1.3	1.5	2.1	1.0	13.5	1.5	2.5	7.8	0.0	22.0
1700-1800	Pro	1.3	20.7	43.0	1.3	12.8	13.8	0.3	2.6	0.0	4.3
	Ocp	1.0	1.8	2.0	2.3	15.4	1.9	1.0	8.4	0.0	18.0
1800-1900 Peak hour	Pro	1.9	18.3	55.2	0.0	12.0	6.9	0.0	1.9	0.0	3.8
	Ocp	1.0	1.5	2.2	0.0	15.9	1.7	0.0	9.0	0.0	40.6
1900-2000	Pro	1.1	19.6	53.5	0.7	13.9	4.6	1.1	2.1	0.0	3.4
	Ocp	1.0	1.7	2.1	2.0	15.9	1.5	1.3	5.7	0.0	23.3
2000-2100	Pro	1.3	20.2	58.9	0.4	11.0	2.2	0.0	2.2	0.0	3.7
	Ocp	1.0	1.5	1.8	4.0	13.5	2.2	0.0	7.2	0.0	10.4
2100-2200	Pro	2.4	9.3	63.5	0.0	14.7	3.4	1.0	1.5	0.0	4.3
	Ocp	1.2	1.7	1.9	0.0	13.9	2.0	1.0	8.7	0.0	9.3
2200-2300	Pro	1.7	19.4	56.7	0.0	14.4	0.0	0.6	1.7	0.0	5.6
	Ocp	1.0	2.3	2.1	0.0	13.2	0.0	1.0	10.7	0.0	6.9
16 hours	Pro	1.2	14.8	52.2	0.5	13.7	10.3	0.8	2.8	0.1	3.8
	Ocp	1.1	1.6	1.9	2.3	14.2	1.6	1.4	7.9	8.0	20.5

Legend

- Pro.** Proportion of vehicles in % (Sum may not add up to 100% due to figure rounding)
- Ocp.** Average occupancy of vehicles
- M&H** Medium and Heavy