


YEAR 2009

CORE STATION 1011






ROAD NETWORK MAJOR

ROAD TYPE PRIMARY DISTRIBUTOR

LINK REPULSE BAY RD & STANLEY GAP RD (from SOUTH BAY RD to TAI TAM RD)



1. TRAFFIC FLOW VARIATION AND GROWTH



2. TRAFFIC CHARACTERISTICS (BY DIRECTION)

Parameter	All - Day	Mon. - Fri.	Sat.	Sun.
SOUTH BOUND				
A.A.D.T.	7890	7980	8510	7150
R 12 / 24 - %	74.2	74.3	73.7	74.3
R 16 / 24 - %	90.9	91.6	89.5	89.4
AM Peak Hour	0700-0800	0700-0800	0900-1000	0900-1000
One-way flow at AM peak hour	420	510	480	370
T - % (AM)	-	-	-	-
PM Peak Hour	1600-1700	1600-1700	1600-1700	1600-1700
One-way flow at PM peak hour	560	570	570	550
T - % (PM)	-	-	-	-
Prop.of commercial vehicles - 16 hr.	-	-	-	-
NORTH BOUND				
A.A.D.T.	7850	7860	8620	7300
R 12 / 24 - %	77.5	78.4	75.2	75.5
R 16 / 24 - %	91.6	92.1	90.7	90.2
AM Peak Hour	0700-0800	0700-0800	0900-1000	0900-1000
One-way flow at AM peak hour	520	650	510	340
T - % (AM)	-	-	-	-
PM Peak Hour	1700-1800	1700-1800	1700-1800	1700-1800
One-way flow at PM peak hour	550	540	610	590
T - % (PM)	-	-	-	-
Prop.of commercial vehicles - 16 hr.	-	-	-	-

3. OTHER INFORMATION AND COMMENT