

YEAR 2010

CORE STATION 5018


ROAD NETWORK MAJOR

ROAD TYPE DISTRICT DISTRIBUTOR

LINK TSING YI NORTH BRIDGE (from TSUEN TSING INT to TAM KON SHAN INT)



1. TRAFFIC FLOW VARIATION AND GROWTH



2. TRAFFIC CHARACTERISTICS (BY DIRECTION)

Parameter	All - Day	Mon. - Fri.	Sat.	Sun.
EAST BOUND				
A.A.D.T.	20080	20190	21490	18680
R 12 / 24 - %	65.9	67.2	65.2	60
R 16 / 24 - %	82.8	83.8	81.7	78.8
AM Peak Hour	0800-0900	0800-0900	0800-0900	0900-1000
One-way flow at AM peak hour	1470	1640	1380	920
T - % (AM)	-	12.9	-	-
PM Peak Hour	1800-1900	1700-1800	1800-1900	1800-1900
One-way flow at PM peak hour	1120	1130	1210	1020
T - % (PM)	-	18.7	-	-
Prop.of commercial vehicles - 16 hr.	-	15.5	-	-
WEST BOUND				
A.A.D.T.	16270	16320	17570	15220
R 12 / 24 - %	60.4	61.7	60.3	53.9
R 16 / 24 - %	80.8	82	79.6	75.6
AM Peak Hour	0800-0900	0800-0900	0900-1000	0900-1000
One-way flow at AM peak hour	880	960	880	560
T - % (AM)	-	21.5	-	-
PM Peak Hour	1800-1900	1800-1900	1800-1900	1800-1900
One-way flow at PM peak hour	1000	1020	1040	880
T - % (PM)	-	14	-	-
Prop.of commercial vehicles - 16 hr.	-	18.5	-	-

3. OTHER INFORMATION AND COMMENT

4. Vehicle classification and occupancy - Monday to Friday

Time		Class of vehicle									
		Motor	Private	Taxi	Private	PLB	Goods veh.		Non	Fr. Bus	
		Cycle	Car		LB		Light	M & H	Fr. Bus	SD	DD
0700-0800	Pro	3.5	16.9	29.7	1.0	10.5	18.3	3.7	6.0	0.2	10.2
	Ocp	1.1	1.6	2.0	3.8	9.7	1.4	1.5	11.1	10.0	37.2
0800-0900	Pro	3.2	28.7	28.0	2.9	6.5	14.9	4.5	4.4	0.2	6.8
	Ocp	1.1	1.4	2.0	7.7	10.0	1.6	1.5	10.2	7.3	47.1
0900-1000	Pro	1.6	26.3	28.3	0.6	7.2	19.5	5.1	1.8	0.1	9.6
	Ocp	1.3	1.4	1.8	4.0	8.1	1.4	1.4	4.1	4.3	23.6
1000-1100	Pro	2.9	19.8	23.6	0.4	5.5	32.9	5.7	1.1	0.2	7.9
	Ocp	1.2	1.4	1.9	2.0	7.7	1.5	1.5	2.8	6.3	22.0
1100-1200	Pro	2.9	19.9	14.6	1.9	8.3	36.2	7.8	0.5	0.2	7.8
	Ocp	1.0	1.5	1.8	2.4	6.9	1.4	1.6	1.0	8.0	24.1
1200-1300	Pro	3.4	22.7	13.6	1.0	8.1	28.2	10.7	3.4	0.3	8.5
	Ocp	1.1	1.5	1.8	2.5	7.2	1.5	1.3	6.7	5.0	22.9
1300-1400	Pro	1.7	23.6	16.3	2.4	8.3	27.9	9.0	2.7	0.2	8.0
	Ocp	1.0	1.6	1.8	2.5	7.7	1.6	1.5	12.9	7.3	26.7
1400-1500	Pro	1.7	25.0	14.5	0.5	7.6	31.2	10.7	1.9	0.2	6.8
	Ocp	1.1	1.6	1.8	4.5	8.1	1.5	1.4	1.8	9.7	21.9
1500-1600	Pro	2.8	21.4	16.0	1.8	7.1	28.8	9.9	2.8	0.2	9.2
	Ocp	1.1	1.5	1.9	2.6	7.6	1.5	1.5	11.7	11.0	21.1
1600-1700	Pro	2.7	18.5	20.9	2.3	8.1	28.8	5.0	5.4	0.2	8.2
	Ocp	1.1	1.7	1.5	6.1	11.6	1.6	1.4	5.1	7.7	28.7
1700-1800	Pro	4.7	24.9	21.4	2.2	6.9	20.8	4.7	5.7	0.2	8.4
	Ocp	1.1	1.6	1.7	2.0	12.2	1.5	1.4	5.5	4.7	33.9
1800-1900	Pro	5.5	33.9	17.7	0.6	7.9	20.1	2.8	3.8	0.2	7.6
	Ocp	1.2	1.5	1.9	1.7	12.8	1.5	1.3	3.2	10.8	42.5
1900-2000	Pro	3.4	42.4	18.9	0.4	7.6	14.0	2.3	3.4	0.1	7.4
	Ocp	1.0	1.6	2.0	1.0	12.7	1.5	1.2	8.3	12.0	33.6
2000-2100	Pro	2.6	40.2	20.6	0.5	9.8	13.0	1.9	1.1	0.2	10.1
	Ocp	1.2	1.6	2.1	2.0	9.0	1.4	1.3	4.3	5.3	22.3
2100-2200	Pro	3.9	36.2	25.7	0.6	9.7	11.3	3.9	0.3	0.2	8.3
	Ocp	1.3	1.5	2.0	1.0	8.4	1.8	1.2	10.0	3.7	22.5
2200-2300	Pro	3.3	38.7	34.1	0.3	7.6	5.1	2.0	0.5	0.2	8.2
	Ocp	1.2	1.8	2.0	1.0	7.2	1.4	1.4	1.0	9.0	22.7
16 hours	Pro	3.1	27.4	21.8	1.2	7.9	21.7	5.4	3.0	0.2	8.3
	Ocp	1.1	1.5	1.9	3.9	9.4	1.5	1.4	7.3	7.6	29.1

Legend

- Pro.** Proportion of vehicles in % (Sum may not add up to 100% due to figure rounding)
- Ocp.** Average occupancy of vehicles
- M&H** Medium and Heavy