YEAR	2011	**LINK**	TSING YI NORTH BRIDGE (from TSUEN TSING INT to TAM KON SHAN INT)
CORE STATION	5018		
ROAD NETWORK	MAJOR		
ROAD TYPE	DISTRICT DISTRIBUTOR		

1. TRAFFIC FLOW VARIATION AND GROWTH

All day — Mon.- Fri. — Sat. — Sun.

2. TRAFFIC CHARACTERISTICS (BY DIRECTION)

Parameter	All - Day	Mon. - Fri.	Sat.	Sun.
EAST BOUND				
A.A.D.T.	20280	20330	21840	18950
R 12 / 24 - %	65.7	66.8	65	60.3
R 16 / 24 - %	82.5	83.4	81.7	78.9
AM Peak Hour	0800-0900	0800-0900	0800-0900	0900-1000
One-way flow at AM peak hour	1460	1620	1390	950
T - % (AM)	-	15.6	-	-
PM Peak Hour	1700-1800	1700-1800	1800-1900	1800-1900
One-way flow at PM peak hour	1150	1170	1230	1080
T - % (PM)	-	19.5	-	-
Prop.of commercial vehicles - 16 hr.	-	14.7	-	-
WEST BOUND				
A.A.D.T.	16300	16330	17700	15110
R 12 / 24 - %	60.3	61.5	60.5	53.9
R 16 / 24 - %	80.7	81.9	79.7	75.5
AM Peak Hour	0800-0900	0800-0900	0900-1000	0900-1000
One-way flow at AM peak hour	850	920	880	580
T - % (AM)	-	18.6	-	-
PM Peak Hour	1800-1900	1800-1900	1800-1900	1800-1900
One-way flow at PM peak hour	1020	1040	1050	870
T - % (PM)	-	14	-	-
Prop.of commercial vehicles - 16 hr.	-	18.3	-	-

3. OTHER INFORMATION AND COMMENT

4. Vehicle classification and occupancy - Monday to Friday

Time		Class of vehicle									
		Motor Cycle	Private Car	Taxi	Private LB	PLB	Goods veh.		Non Fr. Bus	Fr. Bus	
							Light	M & H		SD	DD
0700-0800	Pro	3.6	16.9	30.6	1.6	10.5	17.5	3.4	5.8	0.2	10.0
	Ocp	1.1	1.6	2.3	7.4	10.6	1.4	1.2	11.7	7.0	33.0
0800-0900	Pro	3.2	32.6	23.0	1.2	6.6	16.7	5.2	3.8	0.3	7.4
Peak hour	Ocp	1.1	1.3	1.9	5.8	9.4	1.6	1.6	19.1	8.9	40.3
0900-1000	Pro	1.4	30.1	25.2	1.9	7.3	17.5	7.4	0.7	0.2	8.3
	Ocp	1.3	1.5	2.0	2.9	6.9	1.4	1.6	2.8	4.4	20.4
1000-1100	Pro	1.3	24.0	20.9	0.5	9.2	26.5	7.1	1.0	0.3	9.2
	Ocp	1.0	1.4	2.0	1.5	6.9	1.5	1.4	3.5	7.5	20.2
1100-1200	Pro	3.5	24.6	13.6	1.5	8.3	32.6	5.8	1.5	0.2	8.4
	Ocp	1.1	1.4	2.1	1.7	6.9	1.5	1.5	5.2	4.0	21.7
1200-1300	Pro	2.6	23.4	14.3	1.9	8.7	31.8	6.3	3.3	0.3	7.5
	Ocp	1.1	1.7	1.8	5.4	8.4	1.5	1.3	7.3	3.8	18.2
1300-1400	Pro	3.0	23.0	18.9	1.5	10.1	26.8	5.8	2.0	0.1	8.8
	Ocp	1.1	1.6	1.9	2.5	7.6	1.6	1.6	7.6	7.0	21.8
1400-1500	Pro	2.9	22.9	15.8	0.7	6.3	31.9	9.3	2.2	0.2	7.8
	Ocp	1.1	1.5	1.9	3.3	9.8	1.5	1.4	2.8	5.7	21.1
1500-1600	Pro	2.2	25.6	15.5	2.2	7.0	28.0	7.5	3.1	0.2	8.6
	Ocp	1.2	1.6	1.9	3.6	9.1	1.7	1.5	6.8	6.3	20.7
1600-1700	Pro	3.1	22.9	21.4	3.9	6.0	24.1	5.8	4.9	0.1	7.8
	Ocp	1.0	1.6	1.5	3.0	12.8	1.5	1.5	8.6	8.0	25.2
1700-1800	Pro	5.6	25.3	19.3	2.9	6.1	19.5	7.1	6.5	0.1	7.5
	Ocp	1.1	1.7	1.9	3.6	12.0	1.6	1.4	6.6	9.0	33.2
1800-1900	Pro	5.3	39.5	15.8	1.1	7.1	17.5	3.8	2.4	0.2	7.3
	Ocp	1.0	1.6	2.0	3.0	14.6	1.4	1.2	3.5	9.8	42.4
1900-2000	Pro	5.4	42.6	18.3	0.2	7.0	12.5	2.8	3.0	0.2	8.0
	Ocp	1.1	1.3	2.1	1.0	11.5	1.5	1.5	12.0	5.7	31.9
2000-2100	Pro	2.9	47.4	22.8	0.0	5.7	11.5	1.8	1.0	0.2	6.7
	Ocp	1.1	1.4	2.3	0.0	9.6	1.9	2.0	2.8	5.5	22.2
2100-2200	Pro	3.6	36.3	27.9	1.1	7.5	12.6	1.7	0.3	0.1	8.8
	Ocp	1.2	1.5	2.2	2.3	8.4	1.5	1.3	1.0	6.0	20.0
2200-2300	Pro	3.7	34.7	31.8	0.5	9.9	7.5	1.3	1.3	0.3	8.8
	Ocp	1.2	1.7	2.5	3.5	8.1	1.6	1.0	3.6	4.6	20.5
16 hours	Pro	3.4	29.8	21.0	1.4	7.6	20.5	5.2	2.8	0.2	8.1
	Ocp	1.1	1.5	2.0	3.7	9.5	1.5	1.5	8.8	6.4	26.6

Legend

Pro. Proportion of vehicles in % (Sum may not add up to 100% due to figure rounding)
Ocp. Average occupancy of vehicles
M&H Medium and Heavy