YEAR	2011	**LINK**	COTTON TREE DRIVE (from QUEENSWAY to SLIP RD TO KENNEDY RD)
COVERAGE (B) STATION	2212		
ROAD NETWORK	MAJOR		
ROAD TYPE	PRIMARY DISTRIBUTOR		

1. TRAFFIC FLOW VARIATION AND GROWTH

All day — Mon.- Fri. — Sat. — Sun.

2. TRAFFIC CHARACTERISTICS (BY DIRECTION)

Parameter	All - Day	Mon. - Fri.	Sat.	Sun.
SOUTH BOUND				
A.A.D.T.	51270	52650	51600	46020
R 12 / 24 - %	67.4	68.9	65.3	61.3
R 16 / 24 - %	89.2	90.7	85.4	84.9
AM Peak Hour	0900-1000	0900-1000	0900-1000	0900-1000
One-way flow at AM peak hour	3140	3490	2730	1890
T - % (AM)	-	3.5	-	-
PM Peak Hour	1800-1900	1800-1900	1800-1900	1800-1900
One-way flow at PM peak hour	3400	3450	3160	3530
T - % (PM)	-	3.3	-	-
Prop.of commercial vehicles - 16 hr.	-	4	-	-
A.A.D.T.	-	-	-	-
R 12 / 24 - %	-	-	-	-
R 16 / 24 - %	-	-	-	-
AM Peak Hour	-	-	-	-
One-way flow at AM peak hour	-	-	-	-
T - % (AM)	-	-	-	-
PM Peak Hour	-	-	-	-
One-way flow at PM peak hour	-	-	-	-
T - % (PM)	-	-	-	-
Prop.of commercial vehicles - 16 hr.	-	-	-	-

3. OTHER INFORMATION AND COMMENT

4. Vehicle classification and occupancy - Monday to Friday

Time		Class of vehicle									
		Motor Cycle	Private Car	Taxi	Private LB	PLB	Goods veh.		Non Fr. Bus	Fr. Bus	
							Light	M & H		SD	DD
0700-0800	Pro	0.8	25.6	50.8	2.8	7.1	4.0	1.2	5.8	0.6	1.4
	Ocp	1.0	1.4	2.3	5.9	11.4	2.2	1.2	14.4	42.4	41.5
0800-0900	Pro	1.9	42.7	40.9	1.2	3.7	4.8	0.3	3.3	0.3	1.0
	Ocp	1.0	1.4	2.0	4.3	12.9	2.2	1.0	7.1	47.8	33.4
0900-1000	Pro	2.2	40.8	39.8	0.3	3.6	9.7	0.6	1.9	0.2	0.8
	Ocp	1.1	1.3	1.9	1.3	10.4	1.9	1.6	2.7	29.7	28.3
1000-1100	Pro	3.4	39.6	38.4	0.5	2.5	11.4	0.8	2.1	0.3	1.0
	Ocp	1.1	1.4	1.8	3.0	8.8	1.8	1.7	3.3	19.9	25.8
1100-1200	Pro	1.5	41.9	36.2	1.0	3.7	11.3	0.1	3.1	0.3	1.0
	Ocp	1.0	1.4	1.9	2.7	8.5	1.9	1.0	4.0	23.4	19.4
1200-1300	Pro	0.7	40.6	41.0	2.0	2.9	7.4	0.9	3.3	0.3	1.0
	Ocp	1.0	1.5	2.3	5.1	7.9	1.8	1.4	8.2	17.4	21.0
1300-1400	Pro	2.5	40.8	40.1	0.1	3.1	9.6	0.6	1.8	0.4	1.0
	Ocp	1.1	1.5	2.1	4.0	8.0	1.8	1.0	6.8	12.2	18.7
1400-1500	Pro	1.3	37.1	40.1	0.5	3.1	12.1	0.8	3.9	0.2	0.9
	Ocp	1.0	1.5	2.1	5.3	9.0	1.8	1.5	10.8	16.7	23.8
1500-1600	Pro	1.2	39.9	41.9	1.1	2.9	9.3	0.0	2.6	0.3	0.8
	Ocp	1.1	1.5	2.2	8.9	7.9	1.8	0.0	8.8	21.7	28.0
1600-1700	Pro	1.4	49.2	34.3	0.7	4.2	5.3	0.1	3.4	0.4	1.0
	Ocp	1.0	1.6	2.2	3.2	8.7	1.8	2.0	5.5	18.3	28.7
1700-1800	Pro	0.6	48.7	38.3	0.6	4.1	3.4	0.0	2.8	0.4	1.0
	Ocp	1.2	1.7	2.2	2.2	9.4	1.4	0.0	7.9	19.5	32.5
1800-1900	Pro	1.2	44.8	45.8	0.4	3.4	1.0	0.1	2.4	0.3	0.5
	Ocp	1.1	1.5	2.2	4.3	11.8	1.6	2.0	5.6	26.4	61.5
1900-2000	Pro	1.5	39.5	50.0	0.2	3.8	1.6	0.0	2.5	0.3	0.7
Peak hour	Ocp	1.0	1.3	2.2	7.5	13.7	1.5	0.0	8.2	26.8	42.7
2000-2100	Pro	1.9	36.6	56.0	0.0	2.3	0.9	0.3	0.9	0.3	0.8
	Ocp	1.1	1.4	1.3	0.0	11.9	1.3	2.0	9.7	13.1	28.5
2100-2200	Pro	1.5	30.5	62.7	0.0	2.9	0.8	0.0	0.3	0.3	1.0
	Ocp	1.1	1.4	2.2	0.0	8.7	1.4	0.0	4.0	8.1	27.5
2200-2300	Pro	2.0	32.5	60.3	0.0	2.4	1.2	0.0	0.2	0.4	1.0
	Ocp	1.0	1.5	2.3	0.0	11.1	1.4	0.0	22.0	7.8	21.8
16 hours	Pro	1.6	39.9	44.4	0.7	3.4	5.9	0.3	2.5	0.3	0.9
	Ocp	1.1	1.5	2.1	4.8	10.2	1.8	1.4	7.7	22.3	29.7

Legend

Pro. Proportion of vehicles in % (Sum may not add up to 100% due to figure rounding)
Ocp. Average occupancy of vehicles
M&H Medium and Heavy