


YEAR 2013

CORE STATION 3025





ROAD NETWORK MAJOR

ROAD TYPE URBAN TRUNK ROAD

LINK LIN CHEUNG RD (from YAU MA TEI INT to CHERRY ST UNDERPASS)



1. TRAFFIC FLOW VARIATION AND GROWTH



2. TRAFFIC CHARACTERISTICS (BY DIRECTION)

Parameter	All - Day	Mon. - Fri.	Sat.	Sun.
NORTH BOUND				
A.A.D.T.	14660	15400	14810	11950
R 12 / 24 - %	65.7	66.8	64.7	60.4
R 16 / 24 - %	87.1	88.2	84.4	83
AM Peak Hour	0800-0900	0800-0900	0900-1000	0900-1000
One-way flow at AM peak hour	840	980	700	490
T - % (AM)	-	13.3	-	-
PM Peak Hour	1800-1900	1800-1900	1700-1800	1700-1800
One-way flow at PM peak hour	1080	1190	980	770
T - % (PM)	-	8.7	-	-
Prop.of commercial vehicles - 16 hr.	-	13.2	-	-
 A.A.D.T.	-	-	-	-
R 12 / 24 - %	-	-	-	-
R 16 / 24 - %	-	-	-	-
AM Peak Hour	-	-	-	-
One-way flow at AM peak hour	-	-	-	-
T - % (AM)	-	-	-	-
PM Peak Hour	-	-	-	-
One-way flow at PM peak hour	-	-	-	-
T - % (PM)	-	-	-	-
Prop.of commercial vehicles - 16 hr.	-	-	-	-

3. OTHER INFORMATION AND COMMENT

4. Vehicle classification and occupancy - Monday to Friday

Time		Class of vehicle									
		Motor Cycle	Private Car	Taxi	Private LB	PLB	Goods veh.		Non Fr. Bus	Fr. Bus	
							Light	M & H		SD	DD
0700-0800	Pro	4.3	28.7	31.7	1.7	0.9	15.8	7.3	7.7	0.1	1.9
	Ocp	1.0	1.3	1.8	9.5	1.0	1.3	1.2	12.8	1.0	38.3
0800-0900	Pro	1.9	46.3	26.0	0.0	0.5	11.8	8.2	2.7	0.0	2.4
	Ocp	1.0	1.3	1.6	0.0	1.5	1.5	1.4	13.1	0.0	40.8
0900-1000	Pro	2.9	42.3	23.8	0.7	0.0	14.3	9.2	4.4	0.1	2.2
	Ocp	1.1	1.4	1.7	1.7	0.0	1.4	1.3	6.8	1.0	17.8
1000-1100	Pro	2.0	29.9	18.2	0.7	2.0	24.5	13.3	6.0	0.0	3.5
	Ocp	1.0	1.6	1.7	3.0	1.0	1.5	1.3	7.4	0.0	8.4
1100-1200	Pro	1.5	25.4	24.3	1.5	1.9	28.7	10.4	4.1	0.0	2.2
	Ocp	1.0	1.5	1.7	7.5	1.0	1.8	1.5	8.3	0.0	17.8
1200-1300	Pro	1.6	32.3	19.2	3.3	0.7	31.0	7.2	3.9	0.0	0.9
	Ocp	1.0	1.6	2.3	6.3	1.0	1.6	1.6	8.5	0.0	28.2
1300-1400	Pro	1.1	28.8	29.6	1.1	0.4	24.0	10.7	3.0	0.0	1.3
	Ocp	1.0	1.5	1.7	6.3	1.0	1.5	1.2	8.8	0.0	38.3
1400-1500	Pro	1.4	40.8	22.6	1.1	0.0	20.9	7.6	4.9	0.0	0.7
	Ocp	1.0	1.6	2.1	2.8	0.0	1.7	1.1	5.7	0.0	33.3
1500-1600	Pro	2.0	42.3	21.7	1.3	0.0	16.8	9.7	5.4	0.0	0.8
	Ocp	1.0	1.5	2.2	4.8	0.0	1.8	1.6	10.9	0.0	32.8
1600-1700	Pro	2.0	42.6	19.3	1.5	0.0	20.3	7.5	5.3	0.0	1.4
	Ocp	1.1	1.7	1.8	4.0	0.0	1.7	1.7	9.9	0.0	35.8
1700-1800	Pro	2.9	41.2	25.5	1.8	0.0	17.1	4.7	5.8	0.0	1.1
	Ocp	1.1	1.6	2.3	8.3	0.0	1.8	1.3	9.9	0.0	73.8
1800-1900 Peak hour	Pro	3.9	50.6	21.5	0.5	0.0	14.8	2.5	4.6	0.0	1.6
	Ocp	1.4	1.5	2.4	5.5	0.0	2.0	1.0	20.4	0.0	85.0
1900-2000	Pro	1.5	56.2	24.1	0.6	0.0	8.3	2.3	5.3	0.1	1.5
	Ocp	1.1	1.5	2.7	1.7	0.0	1.6	1.3	16.1	1.0	39.2
2000-2100	Pro	3.2	50.7	31.2	0.0	0.3	2.8	1.6	7.3	0.0	2.9
	Ocp	1.2	1.5	2.1	0.0	1.0	1.8	1.8	16.7	0.0	20.5
2100-2200	Pro	1.5	47.0	31.4	0.3	0.6	6.4	1.5	10.1	0.1	1.1
	Ocp	1.0	1.3	2.6	1.0	1.0	1.6	1.2	17.9	1.0	28.3
2200-2300	Pro	3.0	53.2	32.2	0.3	0.9	4.5	1.2	3.0	0.2	1.5
	Ocp	1.0	1.4	2.2	1.0	1.0	1.1	1.0	16.4	1.0	20.6
16 hours	Pro	2.3	42.4	24.8	1.0	0.4	15.9	6.3	5.2	0.1	1.7
	Ocp	1.1	1.5	2.1	5.4	1.0	1.6	1.4	12.4	1.0	32.9

Legend

- Pro.** Proportion of vehicles in % (Sum may not add up to 100% due to figure rounding)
- Ocp.** Average occupancy of vehicles
- M&H** Medium and Heavy