

YEAR 2016

CORE STATION 5018


ROAD NETWORK MAJOR

ROAD TYPE DISTRICT DISTRIBUTOR

LINK TSING TSUEN RD (from TSUEN TSING INT to TAM KON SHAN INT)



1. TRAFFIC FLOW VARIATION AND GROWTH



2. TRAFFIC CHARACTERISTICS (BY DIRECTION)

Parameter	All - Day	Mon. - Fri.	Sat.	Sun.
EAST BOUND				
A.A.D.T.	26500	26700	28930	23970
R 12 / 24 - %	64.4	65.6	63.3	59.4
R 16 / 24 - %	81.9	82.8	80.8	78.4
AM Peak Hour	0800-0900	0800-0900	0800-0900	0900-1000
One-way flow at AM peak hour	1760	1950	1670	1260
T - % (AM)	-	12.9	-	-
PM Peak Hour	1700-1800	1700-1800	1700-1800	1700-1800
One-way flow at PM peak hour	1520	1530	1670	1340
T - % (PM)	-	15.9	-	-
Prop.of commercial vehicles - 16 hr.	-	14.5	-	-
WEST BOUND				
A.A.D.T.	15180	15440	15750	13850
R 12 / 24 - %	60.7	62	59	55.8
R 16 / 24 - %	81.7	82.8	79	78.3
AM Peak Hour	0800-0900	0800-0900	0900-1000	0900-1000
One-way flow at AM peak hour	820	920	830	530
T - % (AM)	-	13.8	-	-
PM Peak Hour	1800-1900	1800-1900	1800-1900	1600-1700
One-way flow at PM peak hour	910	940	970	830
T - % (PM)	-	13.2	-	-
Prop.of commercial vehicles - 16 hr.	-	17.1	-	-

3. OTHER INFORMATION AND COMMENT

4. Vehicle classification and occupancy - Monday to Friday

Time		Class of vehicle									
		Motor	Private	Taxi	Private	PLB	Goods veh.		Non	Fr. Bus	
		Cycle	Car		LB		Light	M & H	Fr. Bus	SD	DD
0700-0800	Pro	5.8	21.5	32.5	1.2	8.3	13.2	3.0	5.5	0.0	9.0
	Ocp	1.1	1.4	2.1	2.4	11.9	1.4	1.4	10.9	0.0	36.1
0800-0900 Peak hour	Pro	5.4	31.5	24.9	3.8	5.7	15.5	4.5	2.3	0.0	6.5
	Ocp	1.1	1.3	2.0	6.2	9.9	1.5	1.2	10.7	0.0	45.3
0900-1000	Pro	2.4	26.2	24.3	1.6	8.3	22.3	4.7	2.4	0.0	7.8
	Ocp	1.0	1.3	2.0	2.9	8.9	1.5	1.3	4.7	0.0	25.4
1000-1100	Pro	3.3	22.1	23.8	0.7	7.7	26.0	8.2	0.9	0.0	7.4
	Ocp	1.0	1.3	1.9	1.0	8.2	1.5	1.3	2.8	0.0	21.5
1100-1200	Pro	3.3	22.5	16.3	1.8	9.5	31.5	6.0	1.3	0.0	7.9
	Ocp	1.1	1.3	1.8	2.9	7.8	1.4	1.4	3.2	0.0	20.3
1200-1300	Pro	2.1	26.8	16.6	5.2	8.6	23.5	7.6	2.6	0.0	6.9
	Ocp	1.2	1.3	1.6	5.8	8.4	1.4	1.4	7.1	0.0	20.3
1300-1400	Pro	2.4	25.9	18.6	2.0	7.6	24.7	9.5	1.2	0.0	8.0
	Ocp	1.0	1.4	2.0	2.1	8.8	1.5	1.4	11.2	0.0	23.6
1400-1500	Pro	2.9	23.5	16.7	1.8	8.6	29.5	7.8	1.0	0.0	8.2
	Ocp	1.0	1.3	2.0	1.4	8.4	1.4	1.4	3.0	0.0	20.9
1500-1600	Pro	2.2	26.4	20.3	3.4	8.3	23.0	5.1	2.7	0.0	8.7
	Ocp	1.0	1.4	1.9	3.1	10.7	1.5	1.3	10.6	0.0	23.1
1600-1700	Pro	1.7	24.7	24.3	3.8	6.3	20.5	6.6	4.2	0.0	7.8
	Ocp	1.0	1.3	1.7	5.6	10.8	1.5	1.2	10.2	0.0	24.8
1700-1800	Pro	5.6	28.8	20.0	2.7	8.3	17.5	5.2	2.9	0.0	8.8
	Ocp	1.1	1.4	1.8	2.8	10.9	1.5	1.2	6.6	0.0	33.4
1800-1900	Pro	5.1	36.2	21.6	0.8	8.7	14.6	2.7	2.3	0.0	8.0
	Ocp	1.2	1.4	1.9	1.5	13.1	1.3	1.2	3.3	0.0	43.9
1900-2000	Pro	3.9	37.8	21.9	0.4	6.5	13.9	4.9	2.5	0.1	8.2
	Ocp	1.0	1.7	2.3	1.5	12.1	1.5	1.0	6.1	1.0	31.3
2000-2100	Pro	2.7	38.9	26.8	0.0	6.7	11.9	3.8	1.8	0.0	7.4
	Ocp	1.1	1.7	2.1	0.0	9.1	1.4	1.4	2.8	0.0	24.9
2100-2200	Pro	4.9	41.8	23.5	0.3	7.6	9.0	3.8	0.8	0.0	8.3
	Ocp	1.2	1.6	2.0	3.0	9.1	1.4	1.1	1.3	0.0	26.8
2200-2300	Pro	4.0	34.8	34.5	0.3	8.2	4.8	2.8	1.4	0.0	9.2
	Ocp	1.1	1.8	2.0	1.0	7.6	1.1	1.0	1.2	0.0	23.7
16 hours	Pro	3.7	29.2	23.1	1.9	7.7	18.7	5.3	2.3	0.1	8.0
	Ocp	1.1	1.5	2.0	4.1	9.8	1.4	1.3	7.5	1.0	28.7

Legend

Pro. Proportion of vehicles in % (Sum may not add up to 100% due to figure rounding)*

Ocp. Average occupancy of vehicles including both driver and passengers*

M&H Medium and Heavy

* All traffic data are collected from combined bounds except for one way traffic