

YEAR 2019


Location

Screenline A-A(Urban Railway Line)

Stations on Cordon/Screenline

3001, 3002, 4202, 4203, 4204, 4205, 4206, 4207, 4208, 4221 and 4401

1. TRAFFIC FLOW VARIATION AND GROWTH



2. TRAFFIC CHARACTERISTICS (BY DIRECTION)

Parameter	All - Day	Mon. - Fri.	Sat.	Sun.
EAST BOUND				
A.A.D.T.	266090	274270	276580	228060
R 12 / 24 - %	66.4	67.5	64.7	62.3
R 16 / 24 - %	85.5	86.5	83	82.1
AM Peak Hour	0800-0900	0800-0900	0900-1000	0900-1000
One-way flow at AM peak hour	14710	16730	14230	10270
T - % (AM)	-	9.4	-	-
PM Peak Hour	1800-1900	1800-1900	1800-1900	1700-1800
One-way flow at PM peak hour	16450	17180	16770	13500
T - % (PM)	-	6.8	-	-
Prop.of commercial vehicles - 16 hr.	-	8.7	-	-
WEST BOUND				
A.A.D.T.	245210	250570	257520	218440
R 12 / 24 - %	67.4	68.4	65.3	63.6
R 16 / 24 - %	85.4	86.4	83.1	82.4
AM Peak Hour	0800-0900	0800-0900	0900-1000	0900-1000
One-way flow at AM peak hour	14020	15690	14560	10820
T - % (AM)	-	8	-	-
PM Peak Hour	1800-1900	1800-1900	1800-1900	1800-1900
One-way flow at PM peak hour	15710	16370	15480	13420
T - % (PM)	-	6.2	-	-
Prop.of commercial vehicles - 16 hr.	-	7.7	-	-

3. OTHER INFORMATION AND COMMENT

4. Vehicle classification and occupancy - Monday to Friday

Time		Class of vehicle									
		Motor Cycle	Private Car	Taxi	Private LB	PLB	Goods veh.		Non Fr. Bus	Fr. Bus	
							Light	M & H		SD	DD
0700-0800	Pro	5.3	36.8	23.2	3.9	4.0	13.9	4.2	4.5	0.1	4.0
	Ocp	1.1	1.4	2.1	6.9	11.5	1.4	1.2	14.0	18.6	46.2
0800-0900	Pro	3.6	50.2	18.2	1.6	3.3	14.4	2.9	2.5	0.1	3.2
	Ocp	1.1	1.3	2.1	5.2	12.9	1.6	1.3	15.5	18.7	51.9
0900-1000	Pro	2.5	42.5	20.7	1.2	2.9	20.6	3.9	1.8	0.1	3.6
	Ocp	1.1	1.3	2.0	2.7	11.3	1.5	1.3	9.4	14.8	30.3
1000-1100	Pro	2.5	36.1	24.1	1.3	2.9	24.1	4.4	1.2	0.1	3.3
	Ocp	1.1	1.4	1.9	2.5	8.8	1.5	1.3	10.2	12.2	28.5
1100-1200	Pro	2.8	37.0	24.3	1.5	2.8	22.8	3.9	1.6	0.1	3.1
	Ocp	1.0	1.4	2.0	2.8	9.6	1.4	1.3	10.8	11.7	29.9
1200-1300	Pro	3.0	41.1	22.7	2.0	2.6	20.7	3.2	1.7	0.1	2.9
	Ocp	1.0	1.4	1.9	5.2	10.1	1.5	1.3	12.5	14.1	29.7
1300-1400	Pro	2.5	39.2	23.1	1.9	2.5	22.2	4.0	1.7	0.1	3.0
	Ocp	1.1	1.4	2.0	3.4	10.8	1.5	1.3	7.7	12.4	34.2
1400-1500	Pro	2.7	40.7	22.0	1.2	2.2	22.8	3.9	1.6	0.1	2.8
	Ocp	1.1	1.5	2.0	2.4	11.6	1.5	1.3	5.1	15.1	32.9
1500-1600	Pro	3.0	42.7	20.9	2.5	2.0	20.5	3.7	1.9	0.1	2.8
	Ocp	1.1	1.4	2.0	7.7	11.7	1.5	1.4	12.6	15.2	33.8
1600-1700	Pro	3.4	43.7	20.5	1.9	2.5	19.1	3.5	2.3	0.1	3.0
	Ocp	1.1	1.4	1.9	3.2	13.2	1.5	1.2	9.1	18.5	37.7
1700-1800	Pro	4.8	49.6	18.5	1.4	2.8	15.7	1.9	1.9	0.1	3.3
	Ocp	1.1	1.4	2.0	2.8	14.2	1.5	1.3	8.3	18.6	47.9
1800-1900 Peak Hour	Pro	5.5	54.9	18.6	0.4	3.1	11.3	1.3	1.8	0.1	3.0
	Ocp	1.1	1.4	2.1	2.7	15.6	1.4	1.2	15.2	22.3	64.1
1900-2000	Pro	3.6	56.4	21.9	0.1	3.7	7.9	1.2	1.8	0.1	3.3
	Ocp	1.1	1.4	2.0	1.4	14.0	1.4	1.2	8.9	14.2	48.4
2000-2100	Pro	3.7	52.9	26.9	0.1	3.9	6.5	1.2	1.0	0.1	3.7
	Ocp	1.2	1.4	2.0	2.1	11.0	1.5	1.4	4.6	12.3	34.4
2100-2200	Pro	2.9	47.3	33.3	0.1	4.1	6.3	1.0	1.0	0.1	3.9
	Ocp	1.2	1.4	2.0	3.5	10.6	1.5	1.3	4.8	8.5	31.8
2200-2300	Pro	3.2	49.8	32.4	0.1	4.0	5.0	0.8	0.7	0.1	4.0
	Ocp	1.2	1.5	2.0	1.2	10.7	1.5	1.3	6.3	9.0	32.8
16 hours	Pro	3.5	45.1	22.7	1.4	3.0	16.2	2.9	1.9	0.1	3.3
	Ocp	1.1	1.4	2.0	4.6	11.9	1.5	1.3	10.8	15.1	39.1

Legend: Pro. Proportion of vehicles in % (Sum may not add up to 100% due to figure rounding)*

Ocp. Average occupancy of vehicles including both driver and passengers*

M&H Medium and Heavy

* All traffic data are collected from combined bounds