


YEAR 2020

Location Screenline H-H(Boundary Between the Peak and the rest of Hong Kong Island)

Stations on Cordon/Screenline

2203 and 2205

1. TRAFFIC FLOW VARIATION AND GROWTH



2. TRAFFIC CHARACTERISTICS (BY DIRECTION)

Parameter	All - Day	Mon. - Fri.	Sat.	Sun.
UP BOUND				
A.A.D.T.	13240	14450	13450	8690
R 12 / 24 - %	80.5	81.5	78.7	74.4
R 16 / 24 - %	94.9	95.4	94	92.1
AM Peak Hour	0900-1000	0900-1000	0900-1000	0900-1000
One-way flow at AM peak hour	980	1110	890	540
T - % (AM)	-	2.6	-	-
PM Peak Hour	1800-1900	1800-1900	1600-1700	1600-1700
One-way flow at PM peak hour	990	1110	930	670
T - % (PM)	-	0.6	-	-
Prop.of commercial vehicles - 16 hr.	-	2.6	-	-
DOWN BOUND				
A.A.D.T.	13410	14640	13660	8820
R 12 / 24 - %	81.8	82.8	79.9	75.7
R 16 / 24 - %	95.6	96.2	94.4	92.3
AM Peak Hour	0900-1000	0800-0900	0900-1000	0900-1000
One-way flow at AM peak hour	910	1020	870	550
T - % (AM)	-	2.6	-	-
PM Peak Hour	1700-1800	1700-1800	1800-1900	1800-1900
One-way flow at PM peak hour	1030	1140	1030	680
T - % (PM)	-	3.2	-	-
Prop.of commercial vehicles - 16 hr.	-	3.6	-	-

3. OTHER INFORMATION AND COMMENT

4. Vehicle classification and occupancy - Monday to Friday

Time		Class of vehicle									
		Motor Cycle	Private Car	Taxi	Private LB	PLB	Goods veh.		Non Fr. Bus	Fr. Bus	
							Light	M & H		SD	DD
0700-0800	Pro	4.1	43.0	32.9	1.0	2.3	5.9	3.1	6.4	0.0	1.2
	Ocp	1.1	1.3	2.1	8.5	6.8	2.4	1.2	11.0	0.0	44.0
0800-0900	Pro	4.8	48.0	34.4	0.4	2.7	7.2	0.0	1.5	0.0	1.0
	Ocp	1.0	1.4	1.8	2.5	5.0	2.3	0.0	6.8	0.0	37.8
0900-1000	Pro	2.7	50.8	30.2	0.3	0.4	13.3	1.2	0.6	0.0	0.6
	Ocp	1.0	1.4	1.9	2.0	14.5	1.6	1.2	5.0	0.0	30.1
1000-1100	Pro	2.2	61.3	18.6	0.7	1.1	12.5	2.3	0.6	0.0	0.5
	Ocp	1.0	1.5	1.8	4.4	4.3	1.6	1.2	3.0	0.0	25.4
1100-1200	Pro	0.7	64.5	16.5	0.0	0.9	14.8	1.7	0.4	0.0	0.5
	Ocp	1.0	1.5	1.9	0.0	6.7	1.5	1.0	4.5	0.0	26.3
1200-1300	Pro	1.9	63.0	17.4	0.7	1.0	12.9	1.7	0.9	0.0	0.6
	Ocp	1.1	1.5	1.9	5.2	8.9	1.6	1.5	4.2	0.0	26.0
1300-1400	Pro	2.2	59.4	21.8	0.5	1.3	11.2	1.4	1.7	0.0	0.5
	Ocp	1.0	1.5	1.9	7.0	11.7	1.9	1.8	17.6	0.0	38.4
1400-1500	Pro	1.5	64.0	17.4	0.2	1.3	12.3	0.7	1.9	0.0	0.7
	Ocp	1.2	1.6	2.1	2.0	7.8	1.5	1.5	3.2	0.0	41.4
1500-1600	Pro	2.2	62.2	19.8	0.4	1.3	9.6	1.3	2.6	0.0	0.6
	Ocp	1.0	1.5	1.9	6.0	7.1	1.8	1.2	13.9	0.0	27.7
1600-1700	Pro	0.8	63.1	21.7	0.6	1.3	9.6	1.2	1.3	0.0	0.5
	Ocp	1.0	1.4	2.2	2.0	9.2	1.8	1.4	10.6	0.0	43.1
1700-1800	Pro	2.1	62.5	28.2	0.4	0.6	3.8	0.7	1.2	0.0	0.5
	Ocp	1.1	1.5	2.4	2.6	16.1	2.4	1.0	7.0	0.0	44.8
1800-1900 Peak Hour	Pro	2.1	73.3	21.0	0.0	1.0	1.9	0.0	0.4	0.0	0.3
	Ocp	1.0	1.6	2.1	0.0	13.5	1.3	0.0	17.5	0.0	54.6
1900-2000	Pro	1.5	75.9	16.8	0.7	1.2	2.4	0.4	0.8	0.0	0.4
	Ocp	1.0	1.4	2.0	2.4	15.4	1.3	1.0	13.7	0.0	29.6
2000-2100	Pro	3.5	58.6	33.7	0.0	1.9	0.5	0.0	1.1	0.0	0.7
	Ocp	1.0	1.5	1.9	0.0	7.4	1.0	0.0	11.0	0.0	11.3
2100-2200	Pro	2.5	55.1	38.3	0.0	1.8	1.1	0.5	0.0	0.0	0.7
	Ocp	1.0	1.5	1.7	0.0	4.8	1.0	1.0	0.0	0.0	10.4
2200-2300	Pro	3.5	52.8	39.3	0.4	2.2	1.3	0.0	0.0	0.0	0.4
	Ocp	1.0	1.5	1.9	3.0	6.9	1.7	0.0	0.0	0.0	3.5
16 hours	Pro	2.3	60.5	24.0	0.4	1.3	8.3	1.1	1.4	0.0	0.6
	Ocp	1.0	1.5	2.0	4.5	8.4	1.7	1.3	9.9	0.0	33.9

Legend: Pro. Proportion of vehicles in % (Sum may not add up to 100% due to figure rounding)*

Ocp. Average occupancy of vehicles including both driver and passengers*

M&H Medium and Heavy

* All traffic data are collected from combined bounds