



YEAR	2020	LINK	HENNESSY RD (from LUARD RD to FLEMING RD)
CORE STATION	1029		
ROAD NETWORK	MAJOR		
ROAD TYPE	PRIMARY DISTRIBUTOR		



1. TRAFFIC FLOW VARIATION AND GROWTH



2. TRAFFIC CHARACTERISTICS (BY DIRECTION)

Parameter	All - Day	Mon. - Fri.	Sat.	Sun.
EAST BOUND				
A.A.D.T.	15740	16170	16060	14050
R 12 / 24 - %	60.8	61.5	61.3	55.9
R 16 / 24 - %	79.1	80.2	77.1	74.6
AM Peak Hour	0900-1000	0900-1000	0900-1000	0900-1000
One-way flow at AM peak hour	860	940	850	530
T - % (AM)	-	-	-	-
PM Peak Hour	1600-1700	1600-1700	1600-1700	1600-1700
One-way flow at PM peak hour	840	880	900	650
T - % (PM)	-	-	-	-
Prop.of commercial vehicles - 16 hr.	-	-	-	-
WEST BOUND				
A.A.D.T.	11920	12370	12170	10040
R 12 / 24 - %	64.2	65.1	64.3	58.5
R 16 / 24 - %	83.8	84.6	83.7	79.5
AM Peak Hour	0900-1000	0900-1000	0900-1000	0900-1000
One-way flow at AM peak hour	680	690	800	490
T - % (AM)	-	-	-	-
PM Peak Hour	1700-1800	1700-1800	1800-1900	1800-1900
One-way flow at PM peak hour	670	730	740	480
T - % (PM)	-	-	-	-
Prop.of commercial vehicles - 16 hr.	-	-	-	-

3. OTHER INFORMATION AND COMMENT