


YEAR 2021

COVERAGE (B) STATION 4214





ROAD NETWORK MAJOR

ROAD TYPE PRIMARY DISTRIBUTOR

LINK FERRY ST & FERRY ST <FO> (from WATERLOO RD to SHANTUNG ST)



## 1. TRAFFIC FLOW VARIATION AND GROWTH



— All day    - - - - Mon.- Fri.    ..... Sat.    - . - . - Sun.

## 2. TRAFFIC CHARACTERISTICS (BY DIRECTION)

Parameter	All - Day	Mon. - Fri.	Sat.	Sun.
<b>SOUTH BOUND</b>				
A.A.D.T.	37820	37900	38030	38700
R 12 / 24 - %	64.6	65.7	64.2	59.4
R 16 / 24 - %	81	83	79.7	72.8
AM Peak Hour	0800-0900	0800-0900	0800-0900	0900-1000
One-way flow at AM peak hour	2180	2280	1910	2880
T - % (AM)	-	4.9	-	-
PM Peak Hour	1800-1900	1800-1900	1800-1900	1700-1800
One-way flow at PM peak hour	2090	2180	2250	1670
T - % (PM)	-	2.3	-	-
Prop.of commercial vehicles - 16 hr.	-	4.3	-	-
<b>NORTH BOUND</b>				
A.A.D.T.	33740	35730	32910	25830
R 12 / 24 - %	65.5	66.6	63.7	60.3
R 16 / 24 - %	85	85.9	82.9	81.6
AM Peak Hour	0900-1000	0900-1000	0900-1000	0900-1000
One-way flow at AM peak hour	1710	1880	1560	1040
T - % (AM)	-	12.4	-	-
PM Peak Hour	1800-1900	1800-1900	1700-1800	1600-1700
One-way flow at PM peak hour	2090	2240	2090	1640
T - % (PM)	-	3	-	-
Prop.of commercial vehicles - 16 hr.	-	7.1	-	-

## 3. OTHER INFORMATION AND COMMENT

**4. Vehicle classification and occupancy - Monday to Friday**

Time		Class of vehicle									
		Motor Cycle	Private Car	Taxi	Private LB	PLB	Goods veh.		Non Fr. Bus	Fr. Bus	
							Light	M & H		SD	DD
0700-0800	Pro	10.8	33.1	15.3	1.9	2.8	25.7	7.3	2.1	0.0	1.0
	Ocp	1.1	1.2	1.8	2.7	8.6	1.3	1.2	4.9	0.0	1.0
0800-0900	Pro	9.9	41.0	13.5	1.2	2.8	24.4	4.3	1.8	0.0	1.1
	Ocp	1.0	1.3	1.9	3.3	8.5	1.4	1.4	7.2	0.0	1.0
0900-1000	Pro	7.0	35.7	14.4	0.4	1.6	31.2	6.2	1.3	0.1	2.1
	Ocp	1.0	1.3	1.8	1.2	5.7	1.6	1.3	1.9	1.0	1.0
1000-1100	Pro	3.9	36.1	14.5	0.7	1.3	35.0	6.8	0.6	0.0	1.1
	Ocp	1.2	1.4	1.8	2.4	3.1	1.4	1.3	1.1	0.0	1.0
1100-1200	Pro	4.9	35.8	13.8	1.1	1.1	34.7	6.8	1.1	0.0	0.8
	Ocp	1.0	1.3	2.0	4.9	6.1	1.4	1.3	4.1	0.0	1.0
1200-1300	Pro	4.3	39.6	14.9	1.0	1.2	31.9	5.5	1.1	0.0	0.4
	Ocp	1.1	1.5	1.8	2.9	3.0	1.4	1.3	7.9	0.0	1.0
1300-1400	Pro	5.5	36.1	13.7	1.3	1.3	35.0	5.4	1.6	0.0	0.2
	Ocp	1.1	1.3	1.9	2.6	6.2	1.4	1.2	1.5	0.0	1.0
1400-1500	Pro	4.9	36.5	15.6	0.4	0.6	35.7	5.4	0.7	0.0	0.3
	Ocp	1.0	1.3	1.9	2.5	10.8	1.4	1.3	2.6	0.0	1.0
1500-1600	Pro	4.4	42.8	16.6	0.8	1.5	28.7	4.1	0.7	0.0	0.4
	Ocp	1.1	1.5	1.8	1.7	7.0	1.4	1.4	2.5	0.0	1.0
1600-1700	Pro	6.7	47.5	15.0	0.7	0.9	24.4	3.6	0.4	0.0	0.6
	Ocp	1.1	1.4	1.8	2.6	9.0	1.4	1.3	1.0	0.0	1.0
1700-1800	Pro	9.0	50.3	14.7	0.8	2.0	19.1	2.8	0.4	0.0	0.9
	Ocp	1.1	1.3	1.9	2.1	10.5	1.4	1.4	5.3	0.0	1.0
1800-1900 Peak hour	Pro	9.1	56.1	15.8	0.2	1.9	14.2	1.4	0.7	0.0	0.5
	Ocp	1.1	1.3	1.9	1.5	13.3	1.4	1.2	14.0	0.0	1.0
1900-2000	Pro	7.8	54.8	19.4	0.0	2.4	12.6	1.5	0.7	0.0	0.9
	Ocp	1.1	1.3	1.8	0.0	8.3	1.3	1.6	1.0	0.0	1.0
2000-2100	Pro	6.6	49.3	28.6	0.1	2.4	9.2	1.9	1.0	0.0	0.9
	Ocp	1.2	1.4	1.9	2.0	7.5	1.3	1.2	1.4	0.0	1.0
2100-2200	Pro	6.6	46.0	34.3	0.1	2.3	8.5	1.5	0.1	0.0	0.7
	Ocp	1.2	1.4	1.8	1.0	8.3	1.3	1.2	1.0	0.0	1.0
2200-2300	Pro	6.8	48.1	30.3	0.2	2.2	9.7	2.0	0.5	0.0	0.3
	Ocp	1.1	1.4	1.9	1.5	6.5	1.3	1.2	2.8	0.0	1.0
16 hours	Pro	6.7	43.1	17.6	0.7	1.7	24.3	4.2	0.9	0.1	0.8
	Ocp	1.1	1.4	1.8	2.7	7.9	1.4	1.3	4.3	1.0	1.0

**Legend: Pro.** Proportion of vehicles in % (Sum may not add up to 100% due to figure rounding)\*

**Ocp.** Average occupancy of vehicles including both driver and passengers\*

**M&H** Medium and Heavy

\* All traffic data are collected from combined bounds