


YEAR 2021  
CORE STATION 5037  
ROAD NETWORK MAJOR  
ROAD TYPE EXPRESSWAY

LINK EAGLE'S NEST TUNNEL (from TOLL PLAZA to SOUTH PORTAL)

### 1. TRAFFIC FLOW VARIATION AND GROWTH



### 2. TRAFFIC CHARACTERISTICS (BY DIRECTION)

Parameter	All - Day	Mon. - Fri.	Sat.	Sun.
<b>SOUTH BOUND</b>				
A.A.D.T.	29900	32360	30580	20570
R 12 / 24 - %	79.6	80.8	77.6	72.7
R 16 / 24 - %	91.2	91.9	90	88.2
AM Peak Hour	0800-0900	0800-0900	0900-1000	0900-1000
One-way flow at AM peak hour	3070	3820	2240	1080
T - % (AM)	-	10	-	-
PM Peak Hour	1800-1900	1800-1900	1700-1800	1800-1900
One-way flow at PM peak hour	1780	1900	1830	1360
T - % (PM)	-	10.1	-	-
Prop.of commercial vehicles - 16 hr.	-	13.2	-	-
<b>NORTH BOUND</b>				
A.A.D.T.	31310	34010	31440	21560
R 12 / 24 - %	69.2	70.1	68.9	62.9
R 16 / 24 - %	90.3	91.3	88.1	85.2
AM Peak Hour	0800-0900	0800-0900	0900-1000	0900-1000
One-way flow at AM peak hour	1690	2020	1510	790
T - % (AM)	-	16.2	-	-
PM Peak Hour	1800-1900	1800-1900	1800-1900	1800-1900
One-way flow at PM peak hour	3020	3520	2430	1500
T - % (PM)	-	8.2	-	-
Prop.of commercial vehicles - 16 hr.	-	14	-	-

### 3. OTHER INFORMATION AND COMMENT

**4. Vehicle classification and occupancy - Monday to Friday**

Time		Class of vehicle									
		Motor Cycle	Private Car	Taxi	Private LB	PLB	Goods veh.		Non Fr. Bus	Fr. Bus	
							Light	M & H		SD	DD
0700-0800	Pro	2.4	48.1	13.3	1.6	0.0	17.9	11.2	2.1	0.1	3.4
	Ocp	1.0	1.3	2.0	8.1	0.0	1.2	1.1	16.4	1.0	32.8
0800-0900 Peak hour	Pro	1.8	51.0	16.1	0.5	0.0	18.4	7.8	1.9	0.0	2.5
	Ocp	1.0	1.3	2.0	2.8	0.0	1.4	1.2	21.1	0.0	60.3
0900-1000	Pro	1.0	46.9	17.7	0.3	0.0	20.1	11.4	0.9	0.0	1.7
	Ocp	1.0	1.3	2.0	1.0	0.0	1.4	1.1	5.8	0.0	27.1
1000-1100	Pro	1.6	40.0	17.0	0.5	0.0	25.6	13.4	0.3	0.1	1.6
	Ocp	1.1	1.4	1.7	2.0	0.0	1.3	1.2	1.0	1.0	22.8
1100-1200	Pro	1.4	43.7	11.9	0.4	0.0	24.3	16.3	0.8	0.0	1.3
	Ocp	1.2	1.3	1.9	2.0	0.0	1.3	1.1	1.3	0.0	31.7
1200-1300	Pro	0.9	44.4	15.3	0.5	0.0	21.1	15.5	1.0	0.0	1.3
	Ocp	1.3	1.2	2.0	1.5	0.0	1.3	1.1	1.9	0.0	27.9
1300-1400	Pro	1.4	41.1	13.4	0.6	0.0	26.7	14.9	0.9	0.0	1.1
	Ocp	1.0	1.2	2.0	3.8	0.0	1.3	1.1	1.0	0.0	40.0
1400-1500	Pro	1.3	46.8	12.9	0.4	0.0	21.7	14.0	1.7	0.0	1.4
	Ocp	1.0	1.2	2.0	1.7	0.0	1.3	1.1	4.5	0.0	30.4
1500-1600	Pro	1.7	46.0	11.2	0.1	0.0	22.6	15.6	1.6	0.0	1.4
	Ocp	1.0	1.4	2.0	2.0	0.0	1.3	1.2	16.6	0.0	27.4
1600-1700	Pro	1.6	48.0	12.1	0.6	0.0	24.4	10.8	1.2	0.1	1.3
	Ocp	1.1	1.3	1.8	1.4	0.0	1.4	1.1	1.5	1.0	31.5
1700-1800	Pro	3.8	55.3	11.8	0.0	0.0	18.0	8.7	1.0	0.0	1.3
	Ocp	1.1	1.3	2.1	0.0	0.0	1.4	1.1	9.4	0.0	43.2
1800-1900	Pro	3.0	65.2	12.1	0.1	0.0	10.7	5.0	1.5	0.1	2.3
	Ocp	1.1	1.1	2.0	1.0	0.0	1.2	1.1	8.8	1.0	63.7
1900-2000	Pro	2.1	71.9	12.4	0.0	0.0	6.7	3.5	0.8	0.1	2.5
	Ocp	1.3	1.2	2.1	0.0	0.0	1.4	1.1	5.6	1.0	47.6
2000-2100	Pro	3.8	59.9	16.7	0.0	0.0	7.9	7.4	0.3	0.0	3.8
	Ocp	1.1	1.2	1.8	0.0	0.0	1.3	1.0	1.0	0.0	17.9
2100-2200	Pro	2.3	59.0	18.2	0.0	0.0	8.6	7.5	0.2	0.1	4.1
	Ocp	1.2	1.3	2.0	0.0	0.0	1.3	1.2	1.0	3.0	17.1
2200-2300	Pro	1.9	59.9	20.2	0.0	0.0	7.7	7.7	0.3	0.0	2.4
	Ocp	1.1	1.5	2.0	0.0	0.0	1.5	1.1	1.0	0.0	23.5
16 hours	Pro	2.0	51.9	14.3	0.4	0.0	17.9	10.4	1.1	0.1	2.0
	Ocp	1.1	1.3	2.0	3.7	0.0	1.3	1.1	9.9	1.2	37.4

**Legend: Pro.** Proportion of vehicles in % (Sum may not add up to 100% due to figure rounding)\*

**Ocp.** Average occupancy of vehicles including both driver and passengers\*

**M&H** Medium and Heavy

\* All traffic data are collected from combined bounds