


YEAR 2003

COVER AGE (B) STATION 4218






ROAD NETWORK MAJOR

ROAD TYPE DISTRICT DISTRIBUTOR

LINK EASTERN RD & KAI SHING ST (from CONCORDE RD to KAI CHEUNG RD)



1. TRAFFIC FLOW VARIATION AND GROWTH



2. TRAFFIC CHARACTERISTICS (BY DIRECTION)

Parameter	All - Day	Mon. - Fri.	Sat.	Sun.
SOUTH BOUND				
A.A.D.T.	4180	4700	4080	2380
R 12 / 24 - %	72.8	74.7	70.1	58.7
R 16 / 24 - %	86	87.3	82.9	78
AM Peak Hour	0900-1000	0900-1000	0900-1000	0800-0900
One-way flow at AM peak hour	390	480	360	100
T - % (AM)	-	6.3	-	-
PM Peak Hour	1600-1700	1600-1700	1600-1700	1700-1800
One-way flow at PM peak hour	270	310	250	170
T - % (PM)	-	9.8	-	-
Prop.of commercial vehicles - 16 hr.	-	7	-	-
NORTH BOUND				
A.A.D.T.	2660	3020	2470	1530
R 12 / 24 - %	73.9	75.5	73.5	60.6
R 16 / 24 - %	86.5	87.8	85.2	77.5
AM Peak Hour	0900-1000	0900-1000	0800-0900	0800-0900
One-way flow at AM peak hour	170	210	150	70
T - % (AM)	-	22.2	-	-
PM Peak Hour	1600-1700	1700-1800	1600-1700	1800-1900
One-way flow at PM peak hour	190	220	170	100
T - % (PM)	-	6.8	-	-
Prop.of commercial vehicles - 16 hr.	-	11.7	-	-

3. OTHER INFORMATION AND COMMENT

Coverage (B) Station 4218
Year 2003

4. Vehicle classification and occupancy - Monday to Friday

Time		Class of vehicle									
		Motor	Private	Taxi	Private	PLB	Goods veh.		Non	Fr. Bus	
		Cycle	Car		LB		Light	M & H	Fr. Bus	SD	DD
0700-0800	Pro	2.8	11.1	34.6	11.1	0.0	22.1	11.1	5.5	0.0	1.7
	Ocp	1.0	1.0	1.8	4.9	0.0	1.3	1.0	33.5	0.0	19.4
0800-0900	Pro	4.0	29.7	33.6	0.7	0.0	17.8	10.5	3.3	0.0	0.5
	Ocp	1.0	1.4	1.8	5.0	0.0	1.7	1.2	11.8	0.0	54.3
0900-1000 Peak hour	Pro	0.7	46.9	15.6	0.0	0.0	26.5	8.2	1.4	0.0	0.7
	Ocp	1.0	1.5	1.8	0.0	0.0	1.8	1.4	12.0	0.0	19.0
1000-1100	Pro	1.8	28.4	34.9	1.8	0.0	23.9	7.3	0.9	0.0	0.9
	Ocp	1.0	1.3	1.5	3.0	0.0	1.6	1.0	1.0	0.0	7.8
1100-1200	Pro	0.9	30.1	22.1	4.4	0.0	31.9	8.9	1.8	0.0	0.0
	Ocp	1.0	1.2	1.6	1.6	0.0	1.7	1.1	4.0	0.0	0.0
1200-1300	Pro	1.8	43.9	16.7	5.3	0.0	23.7	7.0	1.8	0.0	0.0
	Ocp	1.0	1.7	1.4	3.8	0.0	1.6	1.4	1.0	0.0	0.0
1300-1400	Pro	2.0	36.0	24.0	6.0	0.0	21.0	7.0	4.0	0.0	0.0
	Ocp	1.0	1.5	1.5	9.7	0.0	1.8	1.1	5.5	0.0	0.0
1400-1500	Pro	1.9	34.0	26.2	4.9	0.0	23.3	5.8	3.9	0.0	0.0
	Ocp	1.0	1.5	1.5	5.2	0.0	1.5	1.7	4.3	0.0	0.0
1500-1600	Pro	2.0	37.3	22.2	4.0	0.0	27.2	6.0	1.0	0.0	0.3
	Ocp	1.0	1.4	1.4	3.0	0.0	1.5	1.3	1.0	0.0	1.0
1600-1700	Pro	3.0	24.8	42.4	1.2	0.0	20.6	4.8	3.0	0.0	0.2
	Ocp	1.2	1.4	1.4	2.5	0.0	1.5	2.0	6.6	0.0	1.0
1700-1800	Pro	2.8	41.6	25.4	2.8	0.0	18.3	3.5	4.9	0.0	0.7
	Ocp	1.0	1.4	1.5	1.8	0.0	1.6	1.2	1.0	0.0	11.5
1800-1900	Pro	2.5	36.7	35.0	1.7	0.0	15.8	4.2	3.3	0.0	0.8
	Ocp	1.0	1.6	1.6	1.5	0.0	1.9	1.0	9.5	0.0	24.3
1900-2000	Pro	2.1	42.8	41.8	1.0	0.0	11.5	0.0	0.0	0.0	0.8
	Ocp	1.0	1.8	1.5	2.0	0.0	1.4	0.0	0.0	0.0	18.3
2000-2100	Pro	11.2	43.2	35.2	0.0	0.0	9.6	0.0	0.0	0.0	0.8
	Ocp	1.1	1.4	1.7	0.0	0.0	1.8	0.0	0.0	0.0	15.0
2100-2200	Pro	9.7	29.0	48.4	0.0	0.0	9.7	0.0	3.2	0.0	0.0
	Ocp	1.0	1.7	1.9	0.0	0.0	2.0	0.0	2.0	0.0	0.0
2200-2300	Pro	0.0	18.2	72.7	1.8	0.0	7.3	0.0	0.0	0.0	0.0
	Ocp	0.0	1.5	1.5	1.0	0.0	1.5	0.0	0.0	0.0	0.0
16 hours	Pro	2.6	34.3	30.9	2.8	0.0	20.6	5.9	2.5	0.0	0.5
	Ocp	1.0	1.5	1.6	4.1	0.0	1.6	1.3	8.3	0.0	19.3

Legend

Pro. Proportion of vehicles in % (Sum may not add up to 100% due to figure rounding)
Ocp. Average occupancy of vehicles
M&H Medium and Heavy