

**INFORMATION DOCUMENT
FOR PRIVATE CAR TYPE-APPROVAL**

TA001_{M1}

☐ Initial type approval	☐ Extension of a type of vehicle Previous TA no. 	☐ Extension for modification Previous TA no.
---	---	---

Any drawings must be supplied in appropriate scale and in sufficient detail on size A4, or on a folder of A4 format. Photographs, if any, must show sufficient detail. Submissions in soft copy format are acceptable. If the systems, components or separate technical units have electronic controls, information concerning their performance must be supplied.

Note: The information item printed in *Italic* shall also be completed if available.

0. GENERAL

0.1.	Make (trade name of manufacturer):	
0.2.	Type (multiple entries under one type is allowed):	
	Variant/ Version/ Model Code ⁽¹⁾ (Only list out model under this application):	
0.2.1.	Commercial Name or Model Name or Sale Designation:	
0.3.	Means of identification of type, if marked on the vehicle ^(b) :	
0.3.1.	Location of that marking:	
0.4.	Category of vehicle:	
0.5.	Name and address of manufacture:	
0.5.a.	Name and address of manufacturer's local authorized representative and his C & E ID , if any:	
0.6.	Location of the statutory plates (if any):and	
0.6.a.	Location of the vehicle identification number (enter details in Section 9.17.):	
0.6.b.	The serial numbering of the type begins with no.:	
0.8.	Address(es) of assembly plants(s):	

1. GENERAL CONSTRUCTION CHARACTERISTICS OF THE VEHICLE

1.1.	Photographs and drawings of a representative vehicle:	
1.3.	Number of axles:and wheels:	

2. MASSES AND DIMENSIONS (in kg and mm) (Refer to drawing where applicable)

2.1.	Wheelbase(s) (fully loaded):	
2.3.1.	Track of each steered axle:	
2.3.2.	Track of all other axles:	
2.4.	Range of vehicle dimensions (overall)	
2.4.2.	For chassis with bodywork	
2.4.2.1.	Length:	
2.4.2.2.	Width:	
2.4.2.3.	Height:	
2.6.	Mass of the vehicle ^(o) : (maximum and minimum for each variant):	

2.6.1.	Distribution of this mass among the axles (maximum and minimum for each variant): 1 2 etc (if available)	
2.8.	Technically permissible maximum laden mass ^(Z2) stated by the manufacturer ^(*) :	
2.8.1.	Distribution of this mass among the axles ^(*) : 1 2 etc (if available)	
3. POWER PLANT		
3.1.	Manufacturer (Make):	
3.1.1.	Manufacturer's engine code as marked on engine (Type):	
3.1.1.c	Emission approval reference: (Please enclosed EPD's Approval letter)	
3.2.	Internal combustion engine	
3.2.1.1.	Working principle:	
3.2.1.2.	Number and arrangement of cylinders:	
3.2.1.3.	Engine capacity:	
3.2.1.8.	Maximum power output at speed:	
3.2.9	Exhaust system	
3.2.9.2	Description and/or drawing of the exhaust system:	
3.2.12.2.1.	Catalytic converter	
	Identification Code (same as those stated in VECA in your first application, if applicable)	
3.2.12.2.7.	On-board-diagnostic (OBD) system	
3.2.15.	LPG fueling system:	
3.2.15.1.	Type-approval number: (Please enclosed EMSD's Approval letter)	
3.3. Electric Motor		
3.3.1.	Type (winding, excitation):	
3.3.1.1.	Maximum hourly output:	kW
	Maximum 30-minutes power according to ECE R85:	kW
3.3.1.2.	Operating voltage:	V
3.3.1.3.	Driving range	km
3.3.2. Battery		
3.3.2.1.	Number of cells/modules: cells modules	
3.3.2.2.	Mass:	kg
3.3.2.3.	Capacity:	Ah V kW
3.3.2.5.	Position:	
3.3.3 Charging		
3.3.3.1.	Charging standard	
3.3.3.2.	Charging Current (Standard / Medium / Quick)	A A A
	Charging time (Standard / Medium / Quick)	Hrs Hrs Hrs
	Charging Mode Options	
3.3.3.3.	Vehicle Inlet	
3.3.3.4.	Supply Voltage	
3.4. Other engines or motors or combinations thereof (particulars regarding the parts of such engines or motors)		
3.4.1.	Hybrid electric vehicle:	
3.4.2.	Category of Hybrid electric vehicle:	
4. TRANSMISSION		

4.5.

Gearbox(Make and Type) :

4.5.1. Type (manual/automatic/CVT (continuously variable transmission)) ⁽¹⁾

4.6. Gear ratios

Gear	Internal gearbox ratios (ratios of engine to gearbox output shaft revolutions)	Fianl drive ratio(s) (ratio of gearbox output shaft to driven wheel revolutions)	Total gear ratios
Maximum for CVT *			
1.			
2.			
3.			
...			
Minimum for CVT *			
Reverse			
* Continuously variable transmission.			

4.7. Maximum vehicle speed (in km/h)(A 5% tolerance is permitted):

4.8. Speedometer Make(s)/ Type(s):

4.8.1. *Method of operation and description of drive mechanism:*4.8.2. *Instrument constant of the speedometer: e.g. plus per km*4.8.3. *Tolerance of the measuring mechanism of the speedometer:*4.8.4. *Overall transmission ratio or equivalent data:*4.8.5. *Diagram of the speedometer scale or other forms of display:***6. SUSPENSION**

6.2. Suspension Type):

Axle 1:

Axle 2:

6.6. Tyres and wheels (including all options)

6.6.1. Tyre/Wheel combination(s) (for tyres indicate size designation, minimum load-capacity index, minimum speed category symbol; for wheels indicate rim size(s) and off-set(s))

6.6.1.1. Axles

6.6.1.1.1. Axle 1:

6.6.1.1.2. Axle 2:

7. STEERING (Make and Type):**8. BRAKES**

8.1. Type and characteristics of the brakes with a drawing:

8.2. Operating diagram, description and/or drawing of

8.2.1. Service braking system:

8.2.2. Secondary braking system:

8.2.3. Parking braking system:

8.2.4. Any additional braking system (if fitted):

8.5. Anti-lock braking system: yes/ no ⁽¹⁾**9. BODYWORK**

9.3. Occupant doors, latches and hinges

- 9.3.1. Door configuration and number of doors: _____
- 9.5. Windscreen and other windows
- 9.5.1. Windscreen
- 9.5.1.1. Materials used (e.g. safety glass, safety plastic etc.) and standard (ECE, BS): _____
- 9.5.2. Other windows
- 9.5.2.1. Materials used (e.g. safety glass, safety plastic etc.) and standard (ECE, BS): _____
- 9.12. Safety belts and/or other restraint systems
- 9.12.1. Number and position of safety belts and restraint systems and seats on which they can be used:

		Declare the Type-approval mark (e.g. ECE, BS, EC etc)	Variant (if applicable)	Belt adjustment device for height (indicate yes/no/optional)
First row of seats	L			
	C			
	DR			
Second row of seats *	L			
	C			
	R			
Third row of seats *	L			
	C			
	R			
L = left-hand side; R = right-hand side; C = center; DR = Driver seat * The table may be extended as necessary for vehicle with more than two rows of seats or if there are more than three seats across the width of the vehicle				

- 9.12.2. Nature and position of supplementary restraint systems (indicate yes/ no /optional)

		Front airbag	Side airbag	Belt preloading device
First row of seats	L			
	C			
	DR			
Second row of seats *	L			
	C			
	R			
Third row of seats *	L			
	C			
	R			
L = left-hand side; R = right-hand side; C = center; DR = Driver seat * The table may be extended as necessary for vehicle with more than two rows of seats or if there are more than three seats across the width of the vehicle				

- 9.13. Safety belt anchorages **(Please enclosed a test certificate)**
- 9.13.1. *Photographs and/or drawings of the bodywork showing the position and dimensions of the actual and the effective anchorages including the R-points: (if available)*
- 9.17. Statutory plates (if any) and vehicle identification number
- 9.17.1. Photographs and/or drawings of the locations of the statutory plates and inscriptions and of the vehicle identification number:
- 9.17.2. Photographs and/or drawings of the official part of the plates and inscriptions (completed example with dimensions):
- 9.17.3. Photographs and/or drawings of the chassis number (completed example with dimensions):
- 9.17.4. Manufacturer's declaration of compliance with the requirement
- 9.17.4.1 The meaning of characters shall be explained:

10. LIGHTING AND LIGHT-SIGNALLING DEVICES

- 10.1. List of all devices(mentioning the number, type approval marks, colour, the corresponding tell-tale): See chart below
- 10.4. Dipped beam lamps
- 10.4.1. Value of initial adjustment _____ %

10.1	Category	Colour	No.	Circuit-closed tell-tale	Approval mark/ number	Light source*
a	Main-beam Headlamp					
b	Dipped-beam Headlamp					
c	Front Retro reflectors					
d	Front position lamps					
e	Direction indicator lamps-- Front: Side: Rear:					
f	Hazard warning signal					
g	Rear Position lamps					
h	Stop lamps High Mounted					
i	Rear registration plate lan					
j	Reversing lamps					
k	Rear Retro reflectors					

Optional device (if present)

l	Front fog lamps					
m	Daytime running lamps					
n	Cornering lamps					
o	Parking lamps					
p	End-outline marker lamps					
q	Side marker lamps					
r	Side Retro reflectors					
s	Rear fog lamps					

This table can be extended to suit.

*Light Source: "F" for filament lamp. "H" for HID lamp: "L" for LED

Summary of the construction standards and certificates

Item No.	Subject*	Standard	Certificate and test report Ref. No.	Remarks
3.1.1c	Sound level (e.g. 70/157/EEC, ECE 51...)			
3.1.1c	Exhaust emission (e.g. 70/220, 715/2007, ECE 83...)			
4.8	Speedometer (e.g. 70/220, 715/2007, ECE 83...)			
9.3	Door lock			
9.5	Safety glass (e.g. ECE 43...)			
9.12	Seat belts (e.g. ECE 16...)			
9.13	Seat belt anchorages (e.g. ECE 16...)			
10.1	Installation of lighting and signaling devices (e.g. ECE 48...)			
a, b	Headlamps (e.g. ECE 98, 112, 113,			
c	Front retro reflector (non-triangle)			

d, g, h, m, q, p	Front position lamps, rear position lamps, stop lamps, daytime running lamps, side maker lamp, end-outline marker lamps, (e.g. ECE 7, 87, 91...)			
e,f	Direction indicator (e.g. ECE 6...)			
	Front			
	Side			
	Rear			
i	Rear registration plate lamp			
j	Reversing lamp (e.g. ECE 23)			
k	Rear retro reflector (non-triangle)			
l	Front fog lamps			
n	Cornering lamp (e.g. ECE 119...)			
o	Parking lamp (e.g. ECE 77)			

r	Side retro reflector (non-triangle)			
s	Rear fog lamp			

If those data required in this form is available in your test report/ certificate whilst you can provide a hyperlink in this form to the test report and certificate in CD-ROM accomplished with this application, you are not required to repeat the data entry in this form.

* Delete if not applicable

Authority Signature

Post

Company

Date :

: _____

: _____

: _____

: _____

Company chop

(Edition with Electric Motor: 04/2023)

Note

- (*) Please fill in here the upper and lower values for the variant
- (1) Delete where not applicable (there are cases where nothing need be deleted when more than one entry is applicable).
- (b) If the means of identification of type contains characters not relevant to describe the vehicle, component or separate technical unit types covered by this information document, such characters shall be represented in the documentation by the symbol "?" (e.g. ABC??123??).
- (c) Classified according to the definitions listed in Annex 7 to the Consolidated Resolution on the Construction of Vehicle (R.E.3) or the vehicle approval standard in building such vehicle (e. M1/EU, Passenger Motor Vehicle//Japan etc.).
- (o) Mass of the vehicle with bodywork (if applicable) in running order including coolant, oils, fuel, spare wheels, tools and driver. The mass of the driver is 75 kg (according to ISO Standard 2416-1992) and the fuel tank is filled to 90 % and the other liquid containing systems (except those for used water) to 100 % of the capacity specified by the manufacturer.
- (Z2) Technically permissible maximum laden mass (M)' means the maximum mass of the vehicle based on its construction and performance, stated by the manufacturer.
- (Z9) Technically permissible maximum laden mass of the combination (MC)' means the maximum value of the sum of the masses of the laden motor vehicle and of the laden towed trailer, based on the construction of the motor vehicle, and as stated by the manufacturer.